



MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530056	15052-1A	2 FT 8 IN	1 FT ± 1 IN	AUTO
1301530068	15052-6A	7 FT 8 IN	6 FT ± 2 IN	AUTO
1301530061	15052-25A	26 FT 8 IN	25 FT ± 2 IN	AUTO
1301530065	15052-50A	51 FT 8 IN	50 FT ± 4 IN	AUTO
1301530059	15052-1M	2 FT 8 IN	1 FT ± 1 IN	MANUAL
1301530070	15052-6M	7 FT 8 IN	6 FT ± 2 IN	MANUAL
1301530063	15052-25M	25 FT 8 IN	25 FT ± 2 IN	MANUAL
1301530066	15052-50M	50 FT 8 IN	50 FT ± 4 IN	MANUAL

**TECHNICAL:**

LISTED: UL AND cUL  
 RATED SUPPLY VOLTAGE: 120 VAC  
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING  
 RESET TYPE: AUTOMATIC OR MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS

SYMBOLS DIMENSION UNITS SCALE INCH NTS GENERAL TOLERANCES (UNLESS SPECIFIED) 4 PLACES ± 0.13 ± 0.01 3 PLACES ± 0.25 ± 0.02 2 PLACES ± 0.13 ± 0.01 1 PLACE ± 0.25 ± 0.02 0 PLACES ± 0.13 ± 0.01 ANGULAR TOL ± 0.5° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: MIGRATION TO ECTR/NX EC NO: 629866 DRWN: PPURSUTANDEL 2019/11/11 CHK'D: DNGUYEN62 2020/01/09 APPR: HKNEELAND 2020/02/05 INITIAL REVISION: DRWN: HRUIZ01 2013/02/07 APPR: JFMURPHY 2015/04/20			
	PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: SD-130153-016 DOC TYPE: PSD DOC PART: 001 REVISION: A1					
MATERIAL NUMBER: SEE TABLE CUSTOMER: NORTH SHORE SAFETY SHEET NUMBER: 1 OF 1		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS THIRD ANGLE PROJECTION DRAWING: D-SIZE SERIES: 130153				