



			1		
	Part Number:		DRAWN	12/9/2016	
	TD11/	105-2	CJ		
	IPII		CHECKED	12/9/2016	
			P.D		
	Description:	ransducer	APPROVED	12/9/2016	
	FIEZU III		J.S		

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions						
Sound Pressure Level	75	dB (@ 10cm)						
Resonant Frequency	4,100	Hz						
Rated Voltage	5	V						
Voltage Range	1 ~ 25	V		REVISION HISTORY				
Capacitance	12,000	pF	REV	DESCRIPTION	DATE	APPROVED		
Max. Rated Current	3	mA		Released from Engineering	12/9/2016	J.S.		
Storage Temperature	-40 ~ +85	°C		NOTES				
Operating Temperature	-20 ~ +70	°C		All dimensions are in mm unless otherwise noted				
Connection Method	Surface Pads			2) All tolerances are ± 0.5 mm unless otherwise noted				
Mount Type	Surface Mount			3) All parts meet RoHS				
Housing Material	LCP			4) Subject to change or redrawn without notice				
Weight	0.25	g						
4 3 Additional considerations can be found at www.dbunlimitedco.com/technical-a								