







Color:

Subject to changes. Please also observe the further product documentation!



### Item description

This digital input module receives control signals from field devices (e.g., sensors).

Each input module has a noise-rejection filter with a time constant.

Field and system levels are electrically isolated.

#### Notice:

An additional supply module must be added for 48 VDC supply!

Subject to changes. Please also observe the further product documentation!



## Data

### Technical data

|                                                   |                                                                                                                     |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Number of digital inputs                          | 2                                                                                                                   |
| Total number of channels (module)                 | 2                                                                                                                   |
| Signal type                                       | Digital                                                                                                             |
| Signal type (voltage)                             | 48 VDC                                                                                                              |
| Sensor connection                                 | 2 x (2-wire, 3-wire, 4-wire)                                                                                        |
| Input characteristic                              | high-side switching                                                                                                 |
| Input filter (digital)                            | 3 ms                                                                                                                |
| Input current per channel for signal (1) typ.     | 3.8 mA                                                                                                              |
| Voltage range for signal (0)                      | -6 ... +10 VDC                                                                                                      |
| Voltage range for signal (1)                      | 34 ... 60 VDC                                                                                                       |
| Input data width (internal) max.                  | 2 bits                                                                                                              |
| Supply voltage (system)                           | 5 VDC; via data contacts                                                                                            |
| Current consumption (5 V system supply)           | 2.5 mA                                                                                                              |
| Supply voltage (field)                            | 48 VDC (-15 ... +20 %); via power jumper contacts (power supply via blade contact; transmission via spring contact) |
| Isolation                                         | 500 V system/field                                                                                                  |
| Indicators                                        | LED (A, C) green: Status DI 1, DI 2                                                                                 |
| Number of incoming power jumper contacts          | 3                                                                                                                   |
| Number of outgoing power jumper contacts          | 3                                                                                                                   |
| Current carrying capacity (power jumper contacts) | 10 A                                                                                                                |

### Connection data

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| Connection technology: inputs/outputs | 8 x CAGE CLAMP®                   |
| Connection type 1                     | Inputs/outputs                    |
| Solid conductor                       | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Fine-stranded conductor               | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Strip length                          | 8 ... 9 mm / 0.31 ... 0.35 inches |

### Physical data

|                                   |                        |
|-----------------------------------|------------------------|
| Width                             | 12 mm / 0.472 inches   |
| Height                            | 100 mm / 3.937 inches  |
| Depth                             | 69.8 mm / 2.748 inches |
| Depth from upper-edge of DIN-rail | 62.6 mm / 2.465 inches |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Mechanical Data

|                     |             |
|---------------------|-------------|
| Mounting type       | DIN-35 rail |
| Pluggable connector | fixed       |

## Material Data

|                    |                              |
|--------------------|------------------------------|
| Color              | light gray                   |
| Housing material   | Polycarbonate; polyamide 6.6 |
| Fire load          | 1.397 MJ                     |
| Weight             | 46 g                         |
| Conformity marking | CE                           |

## Environmental requirements

|                                                                                    |                                       |
|------------------------------------------------------------------------------------|---------------------------------------|
| Ambient temperature (operation)                                                    | 0 ... +55 °C                          |
| Ambient temperature (storage)                                                      | -40 ... +85 °C                        |
| Protection type                                                                    | IP20                                  |
| Pollution degree                                                                   | 2 per IEC 61131-2                     |
| Operating altitude                                                                 | 0 ... 2000 m / 0 ... 6562 ft          |
| Mounting position                                                                  | horizontal (standing/lying); vertical |
| Relative humidity (without condensation)                                           | 95 %                                  |
| Vibration resistance                                                               | per IEC 60068-2-6                     |
| Shock resistance                                                                   | 15g per IEC 60068-2-27                |
| EMC immunity to interference                                                       | per EN 61000-6-2                      |
| EMC emission of interference                                                       | per EN 61000-6-4                      |
| Exposure to pollutants                                                             | per IEC 60068-2-42 and IEC 60068-2-43 |
| Permissible H <sub>2</sub> S contaminant concentration at a relative humidity 75 % | 10 ppm                                |
| Permissible SO <sub>2</sub> contaminant concentration at a relative humidity 75 %  | 25 ppm                                |

## Commercial data

|               |                 |
|---------------|-----------------|
| Product Group | 15 (I/O System) |
| eCl@ss 10.0   | 27-24-26-04     |
| eCl@ss 9.0    | 27-24-26-04     |
| ETIM 8.0      | EC001599        |
| ETIM 7.0      | EC001599        |
| Recupel Type  |                 |

Subject to changes. Please also observe the further product documentation!



|                       |               |
|-----------------------|---------------|
| PU (SPU)              | 1 pcs         |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4045454682620 |
| Customs tariff number | 85389099990   |

## Environmental Product Compliance

|                        |                                   |
|------------------------|-----------------------------------|
| RoHS Compliance Status | Compliant, With Exemption         |
| RoHS Exemption         | 6(c)<br>7(a)<br>7(c)-I<br>7(c)-II |

## Approvals / Certificates

### General approvals

| Logo | Approval                                                         | Additional Approval Text | Certificate name            |
|------|------------------------------------------------------------------|--------------------------|-----------------------------|
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle                    | TP TC 020/2011           | EAC RU C-DE.AM02.B.00087/19 |
|      | <b>KC</b><br>National Radio Research Agency                      | Article 58-2, Clause 3   | MSIP-REM-W43-DIM750         |
|      | <b>UL</b><br>Underwriters Laboratories Inc. (ORDINARY LOCATIONS) | UL 508                   | E175199 Sec.1               |

### Declarations of conformity and manufacturer's declarations

| Logo | Approval                                                  | Additional Approval Text | Certificate name |
|------|-----------------------------------------------------------|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

### Approvals for hazardous areas

| Logo | Approval                                      | Additional Approval Text | Certificate name                                 |
|------|-----------------------------------------------|--------------------------|--------------------------------------------------|
|      | <b>ATEX</b><br>TUEV Nord Cert GmbH            | EN 60079-0               | TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc)       |
|      | <b>CCCEX</b><br>CQST/CNEx                     | CNCA-C23-01              | 2020312310000213 (Ex ec IIC T4 Gc)               |
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle | TP TC 012/2011           | EAC RU C-DE.AM02.B.00163/19 (2Ex nA IIC T4 Gc X) |
|      | <b>IECEX</b>                                  | IEC 60079-0              | IECEX TUN 14.0035 X (Ex ec                       |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



|                                                                   |             |                        |
|-------------------------------------------------------------------|-------------|------------------------|
| TUEV Nord Cert GmbH                                               |             | IIC T4 Gc)             |
| <b>INMETRO</b><br>TÜV Rheinland do Brasil Ltda.                   | IEC 60079-0 | BR-Ex_TÜV 12.1297 X    |
| <b>UKEx</b><br>WAGO GmbH & Co. KG                                 | EN 60079-0  | UKCA_WAGO22UKEX003X_ec |
| <b>UL</b><br>Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS) | UL 121201   | E198726 Sec.1          |

## Optional accessories

### Supply module

|                                                             |  |                                                                |
|-------------------------------------------------------------|--|----------------------------------------------------------------|
| Supply module                                               |  |                                                                |
| <b>Item no.: 750-612</b><br>Power Supply; 0 ... 230 V AC/DC |  | <a href="http://www.wago.com/750-612">www.wago.com/750-612</a> |

### Shield termination

|                                                                                                               |  |                                                                |
|---------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------|
| Shield clamping saddles                                                                                       |  |                                                                |
| <b>Item no.: 790-116</b><br>Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm |  | <a href="http://www.wago.com/790-116">www.wago.com/790-116</a> |
| <b>Item no.: 790-124</b><br>Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm |  | <a href="http://www.wago.com/790-124">www.wago.com/790-124</a> |
| <b>Item no.: 790-108</b><br>Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm  |  | <a href="http://www.wago.com/790-108">www.wago.com/790-108</a> |
| <b>Item no.: 790-140</b><br>Shield clamping saddle; diameter of compatible conductor                          |  | <a href="http://www.wago.com/790-140">www.wago.com/790-140</a> |
| <b>Item no.: 790-216</b><br>Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm                                 |  | <a href="http://www.wago.com/790-216">www.wago.com/790-216</a> |
| <b>Item no.: 790-220</b><br>Shield clamping saddle; 30 mm wide; 6 ... 20 mm                                   |  | <a href="http://www.wago.com/790-220">www.wago.com/790-220</a> |
| <b>Item no.: 790-208</b><br>Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm                                  |  | <a href="http://www.wago.com/790-208">www.wago.com/790-208</a> |

### Carrier rail

|                                                                                                                                        |  |                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------|
| Mounting accessories                                                                                                                   |  |                                                                |
| <b>Item no.: 210-197</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored       |  | <a href="http://www.wago.com/210-197">www.wago.com/210-197</a> |
| <b>Item no.: 210-198</b><br>Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored  |  | <a href="http://www.wago.com/210-198">www.wago.com/210-198</a> |
| <b>Item no.: 210-504</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver- |  | <a href="http://www.wago.com/210-504">www.wago.com/210-504</a> |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



colored

**Item no.: 210-505**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored

[www.wago.com/210-505](http://www.wago.com/210-505)**Item no.: 210-506**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored

[www.wago.com/210-506](http://www.wago.com/210-506)**Item no.: 210-508**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored

[www.wago.com/210-508](http://www.wago.com/210-508)**Item no.: 210-113**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

[www.wago.com/210-113](http://www.wago.com/210-113)**Item no.: 210-118**

Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

[www.wago.com/210-118](http://www.wago.com/210-118)**Item no.: 210-112**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored

[www.wago.com/210-112](http://www.wago.com/210-112)**Item no.: 210-114**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-114](http://www.wago.com/210-114)**Item no.: 210-115**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored

[www.wago.com/210-115](http://www.wago.com/210-115)**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-196](http://www.wago.com/210-196)**Marking accessories**

## Marker carrier

**Item no.: 750-103**

Group marker carrier

[www.wago.com/750-103](http://www.wago.com/750-103)

## Marker

**Item no.: 2009-145/000-006**

Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue

[www.wago.com/2009-145/000-006](http://www.wago.com/2009-145/000-006)**Item no.: 2009-145**

Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

[www.wago.com/2009-145](http://www.wago.com/2009-145)**Item no.: 2009-145/000-002**

Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

[www.wago.com/2009-145/000-002](http://www.wago.com/2009-145/000-002)**Item no.: 2009-145/000-007**

Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray

[www.wago.com/2009-145/000-007](http://www.wago.com/2009-145/000-007)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



|                                                                                                                                                   |                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| <b>Item no.: 2009-145/000-005</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red    | <a href="http://www.wago.com/2009-145/000-005">www.wago.com/2009-145/000-005</a> |
| <b>Item no.: 2009-145/000-012</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/2009-145/000-012">www.wago.com/2009-145/000-012</a> |
| <b>Item no.: 2009-145/000-023</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green  | <a href="http://www.wago.com/2009-145/000-023">www.wago.com/2009-145/000-023</a> |
| <b>Item no.: 2009-145/000-024</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet | <a href="http://www.wago.com/2009-145/000-024">www.wago.com/2009-145/000-024</a> |
| <b>Item no.: 248-501/000-006</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue                                    | <a href="http://www.wago.com/248-501/000-006">www.wago.com/248-501/000-006</a>   |
| <b>Item no.: 248-501/000-007</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray                                    | <a href="http://www.wago.com/248-501/000-007">www.wago.com/248-501/000-007</a>   |
| <b>Item no.: 248-501/000-002</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow                                  | <a href="http://www.wago.com/248-501/000-002">www.wago.com/248-501/000-002</a>   |
| <b>Item no.: 248-501/000-012</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange                                  | <a href="http://www.wago.com/248-501/000-012">www.wago.com/248-501/000-012</a>   |
| <b>Item no.: 248-501</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white                                           | <a href="http://www.wago.com/248-501">www.wago.com/248-501</a>                   |
| <b>Item no.: 248-501/000-017</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green                             | <a href="http://www.wago.com/248-501/000-017">www.wago.com/248-501/000-017</a>   |
| <b>Item no.: 248-501/000-005</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red                                     | <a href="http://www.wago.com/248-501/000-005">www.wago.com/248-501/000-005</a>   |
| <b>Item no.: 248-501/000-024</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet                                  | <a href="http://www.wago.com/248-501/000-024">www.wago.com/248-501/000-024</a>   |
| <b>Item no.: 248-501/000-023</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green                                   | <a href="http://www.wago.com/248-501/000-023">www.wago.com/248-501/000-023</a>   |
| <b>Item no.: 750-100</b><br>Marker card; as a DIN A4 sheet; plain                                                                                 | <a href="http://www.wago.com/750-100">www.wago.com/750-100</a>                   |

Subject to changes. Please also observe the further product documentation!



Group marker carrier

**Item no.: 750-106**  
Group marker carrier

[www.wago.com/750-106](http://www.wago.com/750-106)**System housing**

System enclosure

**Item no.: 850-814/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate

[www.wago.com/850-814/002-000](http://www.wago.com/850-814/002-000)

**Item no.: 850-815/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate

[www.wago.com/850-815/002-000](http://www.wago.com/850-815/002-000)

**Item no.: 850-816/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate

[www.wago.com/850-816/002-000](http://www.wago.com/850-816/002-000)

**Item no.: 850-817/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate

[www.wago.com/850-817/002-000](http://www.wago.com/850-817/002-000)

**Item no.: 850-825**  
IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20

[www.wago.com/850-825](http://www.wago.com/850-825)

**Item no.: 850-826**  
IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

[www.wago.com/850-826](http://www.wago.com/850-826)

**Item no.: 850-827**  
IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

[www.wago.com/850-827](http://www.wago.com/850-827)

**Item no.: 850-827/002-000**  
IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

[www.wago.com/850-827/002-000](http://www.wago.com/850-827/002-000)

**Item no.: 850-826/002-000**  
IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

[www.wago.com/850-826/002-000](http://www.wago.com/850-826/002-000)

**Item no.: 850-828/002-000**  
IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

[www.wago.com/850-828/002-000](http://www.wago.com/850-828/002-000)

**Item no.: 850-828**  
IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

[www.wago.com/850-828](http://www.wago.com/850-828)

**Item no.: 850-834**  
IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20

[www.wago.com/850-834](http://www.wago.com/850-834)

**Item no.: 850-835**  
IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable

[www.wago.com/850-835](http://www.wago.com/850-835)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



grip

**Item no.: 850-836**

IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable

[www.wago.com/850-836](http://www.wago.com/850-836)

grip

**Downloads****Documentation****Manual**

|                                                                                        |                          |               |          |
|----------------------------------------------------------------------------------------|--------------------------|---------------|----------|
| System Manual WAGO I/O System 750/753<br>Decentralized Automation Technology           | V 3.3.3<br>2023 年8月29 日  | pdf<br>8.7 MB | Download |
| Product Manual 2-channel, 48VDC, 3.0ms<br>2- to 4-wire connection; high-side switching | V 2.0.0<br>2022 年10月20 日 | pdf<br>2.9 MB | Download |
| System Manual Series 750/753<br>Online HTML                                            |                          | URL           | Download |

**Bid Text**

|                        |              |                |          |
|------------------------|--------------|----------------|----------|
| 750-412<br>X81 - Datei | 2019 年2月19 日 | xml<br>4.2 kB  | Download |
| 750-412<br>doc - Datei | 2017 年7月12 日 | doc<br>27.1 kB | Download |

**Instruction Leaflet**

|                                                                |              |                 |          |
|----------------------------------------------------------------|--------------|-----------------|----------|
| CCC Ex (Additional information)<br>WAGO-I/O-SYSTEM *750-****/* | 2023 年4月26 日 | pdf<br>163.6 kB | Download |
|----------------------------------------------------------------|--------------|-----------------|----------|

**System Description**

|                                                         |  |                 |          |
|---------------------------------------------------------|--|-----------------|----------|
| Overview on WAGO-I/O-SYSTEM 750 approvals               |  | pdf<br>223.5 kB | Download |
| 750/753 Series I/O-System – General Product Information |  | pdf<br>976.2 kB | Download |

**Additional Information**

|                                                                                     |                         |               |          |
|-------------------------------------------------------------------------------------|-------------------------|---------------|----------|
| Disposal and Recycling<br>Electrical and electronic equipment, Batteries, Packaging | V 1.1.0<br>2022 年8月18 日 | pdf<br>2.2 MB | Download |
|-------------------------------------------------------------------------------------|-------------------------|---------------|----------|

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## CAD/CAE-Data

### CAD data

|                      |     |          |
|----------------------|-----|----------|
| 2D/3D Models 750-412 | URL | Download |
|----------------------|-----|----------|

### CAE data

|                           |     |          |
|---------------------------|-----|----------|
| EPLAN Data Portal 750-412 | URL | Download |
|---------------------------|-----|----------|

|                        |     |          |
|------------------------|-----|----------|
| WSCAD Universe 750-412 | URL | Download |
|------------------------|-----|----------|

|                      |     |          |
|----------------------|-----|----------|
| ZUKEN Portal 750-412 | URL | Download |
|----------------------|-----|----------|

## Device Files

### Device Driver

|                                                    |                         |               |          |
|----------------------------------------------------|-------------------------|---------------|----------|
| WAGO USB Service Kabel Treiber / Serie 750 und 857 | 6.5.3.0<br>2014 年9月10 日 | zip<br>4.8 MB | Download |
|----------------------------------------------------|-------------------------|---------------|----------|

## Environmental Product Compliance

### Compliance Search

|                                                                                   |     |          |
|-----------------------------------------------------------------------------------|-----|----------|
| Environmental Product Compliance 750-412<br>2-channel digital input; 48 VDC; 3 ms | URL | Download |
|-----------------------------------------------------------------------------------|-----|----------|

## Installation Notes

### Product family

WAGO I/O System 750/753  
[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.