

Multi fitting keys

45 P PROFI-KEY UNIVERSAL

- > Key for opening and closing of technical shut-off systems e.g. air-conditioning, revision systems
- > For the outdoor areas - locking of bins or waste containers, and street lamp lids etc.
- > With bit insert: slotted head 1.0 x 7 mm and cross-head PH 2 with adapter for 1/4" bits on securing chain
- > 5 mm square for radiator valves
- > Stepped key with 6, 7, 8, 9 mm square
- > Female square 5, 6, 7-8 mm
- > Female three-square 9 mm
- > Dimensions: 90 x 62 mm
- > Zinc die-casting



Measurements	$\frac{mm}{10}$	Code	No.
90 x 62	0.080	2190117	45 P



45 S MULTI FITTING MASTER KEY UNIT

- > Key for opening and closing of master cabinets, switch panels, technical shut-off systems e.g. air-conditioning, revision systems
- > For the outdoor areas - locking of bins or waste containers, and street lamp lids etc.
- > Supplied with bit insert: slotted head 1.0 x 7 mm and cross-head PH 2 with adapter for 1/4" bits on securing chain
- > 5 mm square for radiator valves
- > Female square 5, 6, 7-8 mm
- > Female three-square 9 mm
- > Two-way-key 3-5 mm
- > Dimensions: 72 x 72 mm
- > Zinc die-casting



Measurements	$\frac{mm}{10}$	Code	No.
72 x 72	0.080	2190125	45 S



45 U MULTI FITTING KEY UNIVERSAL

- > For all usual technical shut-off systems
- > 1 tool for 9 applications
- > 8 different master cabinet shut-off systems and 5 mm square for radiator valves
- > Flat construction due to space-saving swivel mechanism
- > Square locking: 5, 6, 7-8, 9-10 mm
- > Three-edged locking: 7, 8-9, 10-11 mm
- > Two-way-key 3-5 mm and half-moon locking 6 mm
- > Securing chain with snap-hook
- > Dimensions: 95 x 95 mm
- > Zinc die-casting



Measurements	$\frac{mm}{10}$	Code	No.
95 x 95	0.204	2294826	45 U



45 E MULTI FITTING KEY ELECTRO

- > For all usual electric master cabinets
- > Space-saving, double swivel mechanism
- > 5 mm square for radiator valves
- > Female square 5, 6, 7-8 mm
- > Female three-square 9 mm
- > Two-way-key 3 - 5 mm
- > Magnetic bit adaptor 1/4", supplied with one bit PH 2
- > Screwdriver function with retaining clip



Measurements	$\frac{mm}{10}$	Code	No.
145	0.120	2294796	45 E




Hook Spanners

40 HOOK WRENCH with lug



- > Acc. to DIN 1810, Form A
- > For slotted round nuts according to DIN 981
- > GEDORE vanadium steel 31CrV3, manganese-phosphated



$\frac{mm}{10}$	L	b	n	t ₁	$\frac{mm}{10}$	Code	No.
16-20	110	2.0	3.8	1.5	0.026	6333990	40 16-20
25-28	135	2.5	4.5	2.0	0.038	6334020	40 25-28
30-32	135	2.5	4.5	2.0	0.043	6334100	40 30-32
34-36	170	3.0	5.5	2.5	0.071	6334290	40 34-36
40-42	170	3.0	5.5	2.5	0.078	6334370	40 40-42
45-50	205	3.5	6.5	3.0	0.133	6334450	40 45-50
52-55	205	3.5	6.5	3.0	0.130	6334530	40 52-55
58-62	240	4.0	7.5	3.5	0.196	6334610	40 58-62
68-75	240	4.0	7.5	3.5	0.208	6334880	40 68-75
80-90	280	5.0	8.5	4.0	0.282	6334960	40 80-90
95-100	280	5.0	8.5	4.0	0.275	6335180	40 95-100
110-115	335	5.0	10.3	4.0	0.491	6335260	40 110-115
120-130	335	5.0	10.3	4.0	0.493	6335340	40 120-130
135-145	385	6.0	12.3	5.0	0.841	6335420	40 135-145
155-165	385	6.0	12.3	5.0	0.820	6335500	40 155-165
180-195	465	6.0	14.3	5.0	1.445	6335690	40 180-195
205-220	465	6.0	14.3	5.0	1.448	6335770	40 205-220