



P.C.B Layout

Specifications:
 Current rating:0.5A AC/DC.
 Voltage rating:40V AC/DC
 Contact resistance:30m ohm Max.
 Insulation resistance: 100M ohm. Min.
 Withstanding voltage:300V AC/minute.
 Operating temperature range:-20°C~+85°C

Material:
 Insulator:High Temp. Plastic(UL94V-0)
 Insulator Color:Black
 Contact:Copper Alloy
 Plated:Gold Plated on Contact Area,
 Tin Plated on Solder Tails.
 Shell:Steel & Copper Alloy, Nickel Plated

RoHS Compliant

| | | | | |
|-----|-------------|------|----|-----------|
| | | | | DRAWN: |
| | | | | CHECKED: |
| | | | | APPROVAL: |
| A | 24-FED-2022 | | | |
| REV | DATE | FILE | BY | |

| |
|---|
| GENERAL TOLERANCE: .X=±0.25 .XX=±0.15 |
| UNIT: MM |
| SCALE:1:1 |
| SHEET: 1 / 2 |
| PROJECTION: |

| | |
|--|-------------------|
| CnC Tech Industrial Cable and Connector Technology | |
| DESCRIPTION: HDMI Receptacle R/A Dip Type | SIZE A4 |
| PART NO: 2000-1-1-20-00-BK | |