

8080 - 1G39 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



8080 - 1G39
(4 - 1437504 - 9)
✔ [Active](#)

Transistor Sockets and Adapters

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- ? Socket
- ? Terminal Style = Solder
- ? Terminal Type = Contact
- ? Lead Size Accepted = 1.52 mm
- ? 3 Terminals

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

? None Available

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

? [Product Line Information](#)

Related Products:

? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Socket
- ? Terminal Type = Contact
- ? Product Series = 8080 - 1G Series

Electrical Characteristics:

? Number of Solder Lugs = 1

Termination Related Features:

? Terminal Plating = Gold

Body Related Features:

- ? Terminal Style = Solder
- ? Number of Terminals = 3
- ? Socket Type = TO -3
- ? Terminal Material = Beryllium Copper
- ? Insulator Material = Diallyl Phthalate

Configuration Related Features:

? Lead Size Accepted (mm [in]) = 1.52 [0.060]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:

? Operating Temperature (°C) = -55 - +125

Other:

? Brand = AMP