

## 73605WS Multi-Conductor - 600V Shielded, Light to Moderate Flexing Applications Up to 1 Million Flex Life Cycles



For more Information  
please call

1-800-Belden1

### General Description:

16 AWG stranded (26x30) bare copper conductors, PVC insulation, oil-resistant PVC inner jacket, tinned copper braid shield, 85% coverage, oil-resistant overall PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
4	16	26x30	BC - Bare Copper	1.524

Total Number of Conductors: 5

#### Ground Wire

Ground Wire (Y/N): Y

Ground Wire AWG: 16

Ground Wire Stranding: 26X30

Ground Wire Conductor Material: BC - Bare Copper

Ground Wire Insulation Material: PVC - Polyvinyl Chloride

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (mm)	Dia. (mm)
PVC - Polyvinyl Chloride	0.559	2.642

##### Insulation Color Code Chart:

Color	Description
Black	Individually Numbered
Yellow/Green	Ground

#### Inner Jacket

##### Inner Jacket Material:

Inner Jacket Material	Nom Wall (mm)	Nom. Dia. (mm)
PVC - Polyvinyl Chloride	0.762	8.915

#### Outer Shield

##### Outer Shield Material:

Outer Shield Material	Coverage (%)
TC - Tinned Copper	85.000

Outer Shield Separator Material: Tissue Tape, 25#37; Overlap, Min.

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.889

#### Overall Cable

Overall Nominal Diameter: 11.405 mm

### Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +90°C

Installation Temperature Range: Flexing: -5°C To +90°C

Operating Temperature Range: Flexing: -5°C To +90°C

Bulk Cable Weight: 403.302 Kg/Km

## METRIC MEASUREMENT VERSION

### 73605WS Multi-Conductor - 600V Shielded, Light to Moderate Flexing Applications Up to 1 Million Flex Life Cycles

<b>Max. Recommended Pulling Tension:</b>	493.750 N
<b>Min. Bend Radius/Minor Axis:</b>	55.880 mm
<b>Min. Bend/Installation:</b>	55.880 mm
<b>Min. Bend Radius (Continuous Flexing):</b>	55.880 mm
<b>Flex Cycle Rating:</b>	1 Million Flexes

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	THHN/THWN Singles
<b>AWM Specification:</b>	UL Style 2587 (600 V 90°C)
<b>CSA Specification:</b>	600 V AWM I/II A/B
<b>EU Directive 2011/65/EU (ROHS II):</b>	Yes
<b>Other Specification:</b>	AWM/STYLE 2587, AWM I/II A/B, FT1, VDE 0472, Section 803 Oil Test, EU Low Voltage Directive 2014/35/EC, EU Directive 2011/65/EU (RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65

### Flame Test

<b>CSA Flame Test:</b>	FT1
------------------------	-----

## Electrical Characteristics (Overall)

### Nom. Inductance:

<b>Inductance (µH/m)</b>
0.591

### Nom. Capacitance Cond. to Other Cond. & Ground:

Description	Freq. (kHz)	Capacitance (pF/m)
Nom. Cond. to Cond	1.000	167.331
Nom. Ground.	1.000	301.852

### Nom. Conductor DC Resistance:

<b>DCR @ 20°C (Ohm/km)</b>
13.452

### Nominal Outer Shield DC Resistance:

<b>DCR @ 20°C (Ohm/km)</b>
8.859

## Put Ups and Colors:

No put ups and colors are available for this product

Revision Number: 0    Revision Date: 09-27-2017

© 2020 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.