

Termination resistor - FL LCX 50-OHM-SMA - 2700425

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



The termination resistor is screwed onto an unused antenna connection of a WLAN device, e.g., in leaky wave applications. This terminates the connection with the correct impedance and prevents undesirable emission.

Product description

Note: In order to screw the FL LCX 50-OHM-SMA termination resistor onto the antenna port (RSMA) of the following devices:

FL WLAN 24 AP 802-11 (Order No. 2884075)

FL WLAN 24 EC 802-11 (Order No. 2884130)

FL WLAN 24 DAP 802-11 (Order No. 2884279)

FL WLAN 230 AP 802-11 (Order No. 2884444)

The RAD-ADP-RSMA/F-SMA/F adapter (Order No. 2884538) is also required.

Key commercial data

Packing unit	1 PCE
Custom tariff number	85366910
Country of origin	China

Technical data

General

Frequency range	2.4 GHz ... 6 GHz
Impedance	50 Ω
Connection method	SMA (male)

Classifications

eCl@ss

eCl@ss 4.0	27240404
eCl@ss 4.1	27240404
eCl@ss 5.0	27242204
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604

Termination resistor - FL LCX 50-OHM-SMA - 2700425

Classifications

ETIM

ETIM 3.0	EC001599
ETIM 4.0	EC000448
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404