


## Small Signal Schottky Diode FlipKY<sup>®</sup> Gen 2



### FEATURES

- Schottky diode for high-speed switching
- Very low dimensions:  
0.6 mm x 0.3 mm x 0.29 mm
- 0.2 A forward current
- Low forward voltage drop (typ. 435 mV at 0.2 A)
- Low reverse current (< 3  $\mu$ A at 10 V)
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### MARKING (example only)



1 = year code

Open circle = month code and pin 1

XY = type code

### LINKS TO ADDITIONAL RESOURCES



### PARTS TABLE

| PART         | ORDERING CODE      | CIRCUIT CONFIGURATION | PACKAGE NAME | TYPE MARKING | WEIGHT   | TAPED UNITS PER REEL (8 mm TAPE ON 7" REEL) | MINIMUM ORDER QUANTITY |
|--------------|--------------------|-----------------------|--------------|--------------|----------|---|------------------------|
| VSKY02300603 | VSKY02300603-G4-08 | Single                | CLP0603-2M   | 23           | 0.115 mg | 15 000                                      | 15 000                 |

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                  | TEST CONDITION        | SYMBOL    | VALUE | UNIT |
|----------------------------|-----------------------|-----------|-------|------|
| Reverse voltage            |                       | $V_R$     | 30    | V    |
| Forward continuous current |                       | $I_F$     | 200   | mA   |
| Surge forward current      | 8.3 ms half sine-wave | $I_{FSM}$ | 6     | A    |
| Power dissipation          | Footprint acc. Fig. 4 | $P_{tot}$ | 278   | mW   |
|                            | Infinite heat sink    |           | 1712  |      |

### THERMAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                                      | TEST CONDITION  | SYMBOL     | VALUE       | UNIT               |
|--|---|------------|-------------|--------------------|
| Thermal resistance junction to ambient air     | Acc. JEDEC <sup>®</sup> 51-3 with footprint acc. Fig. 4 | $R_{thJA}$ | 450         | K/W                |
| Thermal resistance junction to soldering point | Infinite heat sink                                      | $R_{thJS}$ | 73          |                    |
| Maximum operating junction temperature         |   | $T_j$      | 150         | $^{\circ}\text{C}$ |
| Storage temperature range                      |   | $T_{stg}$  | -65 to +150 |                    |

### ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER         | TEST CONDITION                          | SYMBOL | TYP. | MAX. | UNIT          |
|-------------------|---|--------|------|------|---------------|
| Leakage current   | $V_R = 10\text{ V}$                     | $I_R$  |      | 3    | $\mu\text{A}$ |
|                   | $V_R = 30\text{ V}$                     | $I_R$  |      | 10   |               |
| Forward voltage   | $I_F = 10\text{ mA}$                    | $V_F$  | 295  | 350  | mV            |
|                   | $I_F = 100\text{ mA}$                   | $V_F$  | 385  | 460  |               |
|                   | $I_F = 200\text{ mA}$                   | $V_F$  | 435  | 500  |               |
| Diode capacitance | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$ | $C_D$  | 33   |      | pF            |

**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Fig. 1 - Typical Forward Current vs. Forward Voltage at Various Temperatures




Fig. 4 - Typical Thermal Impedance vs. Time




Fig. 2 - Typical Reverse Leakage Current vs. Reverse Voltage at Various Temperatures





Fig. 3 - Typical Capacitance vs. Reverse Voltage


**PACKAGE DIMENSIONS** in millimeters: **CLP0603-2M**


Document no.: S8-V-3906.04-038 (4)  
 Rev.3 - Date: 15. Feb. 2017  
 22825

**Footprint and soldering recommendation:**

please see Application Note: [www.vishay.com/doc?85917](http://www.vishay.com/doc?85917)


**CARRIER TAPE** in millimeters: **CLP0603**



Cummulative tolerances of 10 sprocket holes is  $\pm 0.2$  mm

22591  
Document no. S8-V-3906.04-0025 (4)  
Created - Date: 22. Nov. 2010

**ORIENTATION IN CARRIER CLP0603**



22936

Orientation in Carrier Tape (CLP0603)  
S8-V-3906.04-026 (4)  
22.10.2010



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.