


NOTES:

1. MATERIALS AND FINISHES:
 N STR CRIMP PLUG - BRASS, WHITE BRONZE PLATING
 CABLE - LMR 195
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
3. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 "AMPHENOL RF, 175101-21-XX.XX AND DATE CODE".


THIRD ANGLE PROJ.

REVISIONS

| REV | DESCRIPTION | DATE | ECO | APPR |
|-----|---|-----------|------|------|
| -- | RELEASE TO MFG. | -- | -- | -- |
| B | FORMAT UPDATED, HST LENGTH UPDATED IN LENGTH TABLE, 18.00", 48.00" & METRIC LENGTHS ADDED | 07-Oct-16 | 2005 | AG |



SCALE 0.400



| LENGTH TABLE | | | |
|------------------------|----------------------|-------------------------------|-----------------------------------|
| PART NUMBER (IMPERIAL) | PART NUMBER (METRIC) | LENGTH 'L' IN INCHES [METERS] | LENGTH 'X' IN INCHES [METERS] MIN |
| 175101-21-06.00 | - | 6.00 [0.152] | 0.80 [0.020] |
| - | 175101-21-M0.25 | 9.84 [0.250] | |
| 175101-21-12.00 | - | 12.00 [0.305] | |
| 175101-21-18.00 | - | 18.00 [0.457] | 1.55 [0.039] |
| - | 175101-21-M0.50 | 19.69 [0.500] | |
| 175101-21-24.00 | - | 24.00 [0.610] | |
| - | 175101-21-M0.75 | 29.53 [0.750] | |
| 175101-21-36.00 | - | 36.00 [0.914] | |
| - | 175101-21-M1.00 | 39.37 [1.000] | |
| 175101-21-48.00 | - | 48.00 [1.219] | 157.48 [4.000] |
| - | 175101-21-M2.00 | 78.74 [2.000] | |
| - | 175101-21-M4.00 | 157.48 [4.000] | |

| TOLERANCE TABLE | |
|---------------------------------|----------------|
| LENGTH IN INCHES/FT [METERS] | TOLERANCE |
| 0" - 23.90" [0 - 0.607] | ±0.25" [0.006] |
| 24.00" - 59.00" [0.610 - 1.499] | ±0.50" [0.013] |
| 5.0' - 24.9' [1.524 - 7.617] | ±2.5% |
| 25.0' & UP [7.620 & UP] | ±5.0% |

DESIGN REQUIREMENTS:

- FREQUENCY: ____ TO ____ GHz CONTINUITY
- VSWR ____ : 1 MAX HI-POT : 500 VRMS
- INS. LOSS: ____ dB MAX OTHER

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

| | | | | | |
|---|------------------------------|-----------|-----------|--|---|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0.381 mm) ±.005 (0.127 mm) ± 1° | MATERIAL | DRAWN | DATE | TITLE N STR CRIMP PLUG TO N STR CRIMP PLUG USING LMR-195 CABLE, VARIOUS LENGTH | Amphenol RF www.amphenolrf.com |
| | SEE NOTES | ANANDH G | 04-Jul-16 | | |
| NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. | REFERENCE | ENGINEER | DATE | SCALE: 1.8:1.0 | DRAWING NO. 175101-21-XX-XX ITEM NO. 175101-21-XX-XX PART NO. 175101-21-XX-XX |
| | EAR # 7307 | GOPI M | 28-Mar-12 | SHEET 2 OF 2 | |
| | CONFIGURATION LEVEL: In Work | APPROVED | DATE | DWG SIZE | REV |
| FINISH | K.CAPOZZI | 07-Oct-16 | B | B | |