

Data sheet | Item number: 762-3003

Web Panel; 25.7 cm (10.1"); 1280 x 800 pixels; 2 x USB, 2 x ETHERNET

www.wago.com/762-3003



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Successor model

Item no.762-4104

Touch Panel 600; 25.7 cm (10.1"); 1280 x 800 pixels; 2 x USB, 2 x ETHERNET; Web Panel

www.wago.com/762-4104

Item description

Specifically configured as a Web browser, the Web Panel directly connects to controllers with their own Webservers.

The *e!COCKPIT* (CODESYS 3) or CODESYS 2.3 Web visualization has been specifically optimized for the Web Panel.

Data

Technical data

Display diagonal

25.7 cm (10.1 inches)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Display	Resistive touchscreen
Display colors	16 million colors
Graphics resolution	(1280 x 800) px
Contrast ratio	800:1
Viewing angle (horizontal/vertical)	85° / 85°
Brightness	800 cd/m ²
HBT (Half Brightness Time)	70,000 h
Visualization	Web-Visu Web Visu
ETHERNET protocols	DHCP DNS FTP FTPS HTTP HTTPS SSH
Communication	Web browser (CODESYS2)
Operating system	Linux [®]
Processor	ARM [®] Cortex™ A8 600 MHz
Main memory (RAM)	512 MB
Internal memory (flash)	1024 MB
Type of memory card	microSD (max. 2 GB); microSDHC (max. 32 GB)
Baud rate	ETHERNET: 10/100 Mbit/s
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel, two capacitive keys, proximity sensor
Supply voltage	24 VSELV DC (18 ... 31.2 V); with reverse voltage protection
Input current (max.) (24 V)	390 mA
Operating power	9.9 W (max.)

Connection data

Connection technology: communication/fieldbus	Modbus (TCP): 2 x RJ-45; USB: 2 x USB 2.0 host (type A)
---	---

Physical data

Width	293 mm / 11.535 inches
Height	223 mm / 8.78 inches
Depth	58 mm / 2.283 inches
Panel cutout (W x H)	(278 x 208) mm

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Mechanical Data

Weight	2138 g
Front panel	Anodized aluminum, polyester film
Housing material	Anodized aluminum
Conformity marking	CE

Environmental requirements

Ambient temperature (operation)	0 ... +50 °C
Ambient temperature (storage)	-20 ... +80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)
Fire load	0.003 MJ

Commercial data

eCl@ss 10.0	19-20-01-03
eCl@ss 9.0	19-20-01-03
ETIM 8.0	EC001414
ETIM 7.0	EC001414
Recupel Type	
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143356480
Customs tariff number	84714100000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC RU C-DE.AM02.B.00087

Subject to changes. Please also observe the further product documentation!

KC National Radio Research Agency	Article 58-2, Clause 3	MSIP- REM-W43- WBP762
KC National Radio Research Agency	Article 58-2, Clause 3	MSIP- REM-W43- WBP762
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	PRS Polski Rejestr Statków	-	TE/2190 /880590 /18

Optional accessories**Memory card**

Memory card		
Item no.: 758-879/000-3102 Memory Card SD Micro; 2 GByte		www.wago.com/758-879/000-3102
Item no.: 758-879/000-3108 Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C		www.wago.com/758-879/000-3108

Mounting

Mounting accessories		
Item no.: 762-9001 e!DISPLAY7300T ; Clamping elements (4 pieces)		www.wago.com/762-9001

Downloads**Documentation****Manual**

Subject to changes. Please also observe the further product documentation!



Product Manual e!DISPLAY 7300T, Web Panel WP 10.1 1280x800 PIO 1	V 1.1.0	pdf 2.2 MB	Download
---	---------	---------------	----------

Bid Text

762-3003 X81 - Datei	2019 年2月19日	xml 5.2 kB	Download
762-3003 doc - Datei	2016 年1月8日	doc 30.2 kB	Download

Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 2022 年8月18日	pdf 2.2 MB	Download
---	------------------------	---------------	----------

System Description

Overview on WAGO-I/O-SYSTEM 750 approvals		pdf 223.5 kB	Download
Touch Panel 600, system description		pdf 513.5 kB	Download

Runtime Software

Firmware

0762-300x, e!DISPLAY 7300T WAGO_FW0762-300x_V010204_IX04_I	V 04 2021 年10月19日	zip 99.5 MB	Download
---	----------------------	----------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 762-3003		URL	Download
-----------------------	--	-----	----------

CAE data

EPLAN Data Portal 762-3003		URL	Download
WSCAD Universe 762-3003		URL	Download
ZUKEN Portal 762-3003		URL	Download

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 762-3003

URL

Download

Web Panel; 25.7 cm (10.1""); 1280 x 800 pixels; 2 x USB, 2 x ETHERNET

Installation Notes

Product family

DISPLAY 7300T

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.