

SIMATIC IPC 477E 22" Touch (1920 x 1080); with front USB; 4 USB (back), Ethernet (10/100/1000); Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); 16 GB; without RS 232/RS485; 1x PCIe (x4); Windows7 Ultimate SP1, 64-bit, MUI (de, en, es, fr, it); Without replaceable mass storage; 240 GB solid-state drive SATA Without SIMATIC software; 24 V DC industrial power supply

| General information | |
|---|--|
| Product type designation | IPC477E |
| Display | |
| Design of display | 22" TFT touch |
| Screen diagonal | 21.5 in |
| Resolution (pixels) | |
| • Horizontal image resolution | 1 920 pixel |
| • Vertical image resolution | 1 080 pixel |
| Backlighting | |
| • MTBF backlighting (at 25 °C) | 30 000 h |
| Control elements | |
| Input device | |
| • Mouse, at front | No |
| Keyboard fonts | |
| • Function keys | No |
| • alphanumeric keyboard | No |
| Touch operation | |
| • Design as touch screen | Yes; analog, resistive |
| Installation type/mounting | |
| Mounting | For horizontal and vertical mounting |
| Design | Panel PC, built-in unit |
| central design | Yes |
| distributed design | No |
| Mounting in portrait format possible | Yes |
| Supply voltage | |
| Type of supply voltage | 100/240 V AC (autorange) 50/60 Hz; optional 24 V DC |
| Line frequency | |
| • Rated value 50 Hz | Yes |
| • Rated value 60 Hz | Yes |
| Mains buffering | |
| • Mains/voltage failure stored energy time | 20 ms |
| Power loss | |
| In full configuration | 24 V DC: max. 74 W, PCIe APGB additionally 5 W |
| Processor | |
| Processor type | Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT) |
| Chipset | Intel C236 / Intel H110 |
| Graphic | |
| Graphics controller | Intel HD graphics controller |
| Drives | |
| Hard disk | 2.5" SATA ≥ 320 GB |
| SSD | Yes; 128 / 240 / 480 GB |
| Memory | |
| Type of memory | DDR4-2400 SO-DIMM |
| Main memory | 4 / 8 / 16 GB, ECC optional |
| Capacity of main memory, max. | 16 Gbyte |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; 128 KB can be stored in the buffer time; optional |

| Hardware configuration | |
|---|---|
| Slots | |
| <ul style="list-style-type: none"> • free slots | 1x PCIe (slot with card retainer), 1x slot for CFAST card |
| <ul style="list-style-type: none"> • Number of PCI slots | 1; Optional |
| <ul style="list-style-type: none"> • Number of compact flash slots | 1; CFAST |
| Interfaces | |
| Number of industrial Ethernet interfaces | 3; 3x Ethernet (RJ45) |
| USB port | 4x USB 3.0 |
| Connection for keyboard/mouse | USB / USB |
| serial interface | Without / 2x COM (RS 232 / 422 / 485), selectable in the BIOS |
| Video interfaces | |
| <ul style="list-style-type: none"> • Graphics interface | 2x DisplayPort |
| Industrial Ethernet | |
| <ul style="list-style-type: none"> • Industrial Ethernet interface | 3x Ethernet (RJ45) |
| <ul style="list-style-type: none"> — 100 Mbps | Yes |
| <ul style="list-style-type: none"> — 1000 Mbps | Yes |
| Interrupts/diagnostics/status information | |
| Bus diagnostics | Yes |
| Integrated Functions | |
| Monitoring functions | |
| <ul style="list-style-type: none"> • Temperature monitoring | Yes |
| <ul style="list-style-type: none"> • Watchdog | Yes |
| <ul style="list-style-type: none"> • Fan | No |
| <ul style="list-style-type: none"> • Monitoring function via network | Optional |
| EMC | |
| Interference immunity against discharge of static electricity | |
| <ul style="list-style-type: none"> • Interference immunity against discharge of static electricity | ±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2 |
| Interference immunity against high-frequency electromagnetic fields | |
| <ul style="list-style-type: none"> • Interference immunity against high frequency radiation | 10 V/m, 80 ... 2 000 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 ... 2.7 GHz; 10 V, 10 kHz ... 80 MHz acc. to IEC 61000-4-6 |
| Interference immunity to cable-borne interference | |
| <ul style="list-style-type: none"> • Interference immunity on supply cables | ±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric |
| <ul style="list-style-type: none"> • Interference immunity on signal cables >30m | ±2 kV acc. to IEC 61000-4-5, surge, length > 30 m |
| <ul style="list-style-type: none"> • Interference immunity on signal cables < 30m | ±1 kV acc. to IEC 61000-4-4; burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4; burst; length > 3 m |
| Interference immunity against voltage surge | |
| <ul style="list-style-type: none"> • asymmetric interference | ±2 kV acc. to IEC 61000-4-5, surge asymmetric |
| <ul style="list-style-type: none"> • symmetric interference | ±1 kV acc. to IEC 61000-4-5, surge symmetric |
| Interference immunity to magnetic fields | |
| <ul style="list-style-type: none"> • Interference immunity to magnetic fields at 50 Hz | 100 A/m; to IEC 61000-4-8 |
| Emission of conducted and non-conducted interference | |
| <ul style="list-style-type: none"> • Interference emission via line/AC current cables | EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A |
| Degree and class of protection | |
| IP (at the front) | IP65 |
| IP (rear) | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| <ul style="list-style-type: none"> • UL 508 | Yes |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| FCC | Yes |
| EMC | CE, EN 61000-6-4; CISPR 22:2004 Class A; FCC Class A |
| Use in hazardous areas | |
| <ul style="list-style-type: none"> • ATEX Zone 2 | Yes; Optional, only with Multitouch |
| <ul style="list-style-type: none"> • IECEx Zone 2 | Yes; Optional, only with Multitouch |

| | |
|---|---|
| <ul style="list-style-type: none"> • cULus Class I Zone 2, Division 2 | Yes; Optional, only with Multitouch |
| Marine approval | |
| <ul style="list-style-type: none"> • Germanischer Lloyd (GL) • American Bureau of Shipping (ABS) • Bureau Veritas (BV) • Det Norske Veritas (DNV) • Korean Register of Shipping (KRS) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (Class NK) | Yes Yes Yes Yes Yes Yes Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • min. • max. | 0 °C 45 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> • min. • max. | -20 °C 60 °C |
| Relative humidity | |
| <ul style="list-style-type: none"> • Relative humidity | Tested according to IEC 60068-2-78, IEC 60068-2-30: 5% to 80% at 25 °C (no condensation) |
| Vibrations | |
| <ul style="list-style-type: none"> • Vibration resistance during operation acc. to IEC 60068-2-6 | IEC 60068-2-6; 5 Hz to 9 Hz: 3.5 mm; 9 Hz to 500 Hz: 9.8 m/s ² (with SSD or CFast); 10 Hz to 58 Hz: 0.0375 mm; 58 Hz to 200 Hz: 4.9 m/s ² (hard disk) |
| Shock testing | |
| <ul style="list-style-type: none"> • Shock load during operation | IEC 60068-2-27; 150 m/s ² , 11 ms (without hard disk); 50 m/s ² , 30 ms (with hard disk) |
| Operating systems | |
| pre-installed operating system | Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10 |
| without operating system | Yes; Optional |
| pre-installed operating system | |
| <ul style="list-style-type: none"> • Windows 7 • Windows 10 Enterprise | Yes; Ultimate 64 bit Yes; Windows 10 Enterprise 2016 LTSC, 64 bit, MUI |
| Software | |
| SIMATIC Software | Optionally with pre-installed SIMATIC WinCC RT Advanced / Software Controller CPU 1500S software bundle |
| Dimensions | |
| Width of the housing front | 560 mm |
| Height of housing front | 380 mm |
| Mounting cutout, width | 542 mm |
| Mounting cutout, height | 362 mm |
| Overall depth | 76 mm |
| Weights | |
| Weight, approx. | 9.5 kg |

last modified: 1/31/2021 