

Buchanan WireMate TE Internal #: 5-2834006-3 Poke-In Connectors, Wire-to-Board, 4 mm Centerline, Printed Circuit Board, Height .176 in [4.48 mm], Surface Mount, 18 – 22 AWG Wire Size

View on TE.com >



Connectors > Lighting Connectors > Poke-In Connectors > Poke-In Connector, BUCHANAN WireMate

Connector System: Wire-to-Board

Centerline (Pitch): 4 mm

Connector & Contact Terminates To: Printed Circuit Board

Connector Height: 4.48 mm [.176 in]

Termination Method to Printed Circuit Board: Surface Mount

All Poke-In Connector, BUCHANAN WireMate (51)

Features

Product Type Features

Product Line	Poke-In
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Electrical Characteristics

Operating Voltage	400 VAC
Body Features	
Primary Product Color	Natural
Contact Features	
PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Current Rating (Max)	6 A
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	

5-2834006-3

Poke-In Connectors, Wire-to-Board, 4 mm Centerline, Printed Circuit Board, Height . 176 in [4.48 mm], Surface Mount, 18 – 22 AWG Wire Size



Centerline (Pitch)	4 mm
Dimensions	
Compatible Insulation Diameter Range	2.1 mm
Connector Height	4.48 mm[.176 in]
Wire Size	18 – 22 AWG
Industry Standards	
Agency/Standard	UL
Approved Standards	UL 1977, UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

5-2834006-3

Poke-In Connectors, Wire-to-Board, 4 mm Centerline, Printed Circuit Board, Height . 176 in [4.48 mm], Surface Mount, 18 – 22 AWG Wire Size



TE Part # 2834006-3 RELEASE POKE-IN CONNECTOR_3POLES

Customers Also Bought



TE Part #1734035-4	TE Part #4-1437565-2	TE Part #796642-2	TE Part #5787428-1	
MINI USB, TYPE B, R/A, SMT, MYLAR	FSM4JSMATR=TACT SWITCH	1 6X6MIL 2POS 5.0MM CE VRT HDR,TRM B	BLK HDR ASY,RA,LKEY,STR TAIL	.,12.0V

TE Part #2-2176308-6 RP 1E 0.1W 243K 0.1% 25PPM 5K RL

Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_5-2834006-3_B.2d_dxf.zip

English

Customer View Model

C For support call+1 800 522 6752

5-2834006-3

Poke-In Connectors, Wire-to-Board, 4 mm Centerline, Printed Circuit Board, Height . 176 in [4.48 mm], Surface Mount, 18 – 22 AWG Wire Size



ENG_CVM_CVM_5-2834006-3_B.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_5-2834006-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Modular Releasable Poke-in datasheet

English

BUCHANAN WireMate Connectors Brochure

BUCHANAN WireMate Connectors Brochure

English

Modular Releasable Poke-in datasheet (Chinese)

Product Specifications Application Specification English