



Electrical Characteristics

Nominal Impedance: 60-75 Ohms
 Frequency Range: DC to 900 MHz
 Operating Voltage (DC): 4000 V maximum
 Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
 Contact Resistance: 3.0 milliohms maximum
 Insulation Resistance: 10000 megohms minimum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum

Environmental Characteristics

Temperature Range: -55 °C to +85 °C

	PART	DESCRIPTION
1	Spring	Steel, Tin Plated
2	Body	Steel, Tin Plated
3	Insulator	Glass Fibre
4	Contact	Brass, Tin plated

First Issue	PDC	1	06 Sep 02
DESCRIPTION OF REVISION	APPVD	ISS	DATE



Cinch Connectivity Solutions
 7-13 Russell Way,
 Widford Industrial Estate,
 Chelmsford, Essex,
 CM1 3AA, UK.
 Tel: +44 (0) 1245 359515
 Fax: +44 (0) 1245 358938

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
 ± 0.2mm unless
 otherwise stated

DRAWN BY:

P D Couzens

CHECKED BY:

S Nash

APPROVED BY:

G Dalton

DATE:

06 Sep 02

TITLE:

Euro PCB Mount Jack

PART NUMBER:

VEU334

PAGE: 1 of 1