TE Internal #: 2273107-3

M12 Cable Assembly, 4 Position, 1 m, Sensor/Actuator, Code A,

M12 Plug, M12 Socket, Double Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M12 A-Code Y-Cable Assembly











M8/M12 Application Type: Sensor/Actuator

Number of Positions: 4

Connector & Keying Code: A

Connector Type (End A): M12 Plug

Connector Type (End B): M12 Socket

All M12 A-Code Y-Cable Assembly (10)

Features

Product Type Features

Connector Type (End A)	M12 Plug	
Connector Type (End B)	M12 Socket	
Cable Assembly Type	M12	
Configuration Features		
Number of Positions	4	
Electrical Characteristics		
Operating Voltage	250 VAC	
Body Features		
Cable Color	Black	
Connector Color (End B)	Black	
Connector Color (End A)	Black	
Jacket Material	PUR	
Wire Color (Base)	Brown, White, Blue, Black	



Connector & Keying Code	A	
Contact Features		
Contact Current Rating (Max)	4 A	
Mechanical Attachment		
Thread Size	M12	
Connector Orientation (End A)	Straight	
Connector Orientation (End B)	Straight	
Housing Features		
Housing Material	Plastic	
Dimensions		
Outside Cable Diameter	4.3 mm[.161 in]	
Wire Size	.326 mm²	
Usage Conditions		
Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]	
Operation/Application		
M8/M12 Application Type	Sensor/Actuator	
Shielded	No	
Packaging Features		
Packaging Method	Box	
Other		
Field Serviceable	Yes	
Cable Assembly Length	1 m	

Product Compliance

Cable Assembly Configuration

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223)

Double Ended



	not cont	. DL	$\Lambda \bigcirc I I$	$C \setminus I \setminus I \subset$
	ant cont	210 RE	/1(H	
- レンに3 1		alli ixi	\neg	\mathcal{I}

	alogen - Br, Cl, F, I < 900 ppm per genous material. Also BFR/CFR/PVC
--	--

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





Documents

Product Drawings

M12 Y conn Male to 2xM12 Female A

English

CAD Files

3D PDF



3D

Customer View Model

ENG_CVM_CVM_2273107-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2273107-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2273107-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Product Specification

English