

Product data sheet

Specifications



PLA door 1500x750 with handle

NSYDPLA157HG

Main

| | |
|------------------------------------|-------------------------|
| Range | Thalassa |
| Accessory / separate part category | Enclosure accessory |
| Product or component type | Door |
| Application | Multi-purpose |
| For enclosure nominal dimensions | - |
| Mounting location | Front |
| Range compatibility | Thalassa (Thalassa PLA) |
| Device composition | 1 door locking system |
| Quantity per set | Set of 1 |

Complementary

| | |
|-------------------|--|
| Material | Door: polyester reinforced with fibreglass |
| Colour | Door: grey (RAL 7035) |
| Lock type | Lock 5 mm double bar |
| Number of locks | 1 |
| Door type | Plain |
| Door opening side | Reversible (120 °) Reversible (180 °) |
| Maximum load | 30 kg/m ² |
| Height | 1500 mm |
| Width | 750 mm |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 79.0 cm |
| Package 1 Width | 6.0 cm |
| Package 1 Length | 155.0 cm |

Package 1 Weight 12.55 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

RoHS exemption information [Yes](#)

Environmental Disclosure [Product Environmental Profile](#)

Recommended replacement(s)