

# Product data sheet

Specifications



## Cost-effective LED Lamps - 24/48 V DC - 5W



NSYLAMT5LD1VDC

### Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	1

### Complementary

Outlet standard	Without socket
Rated lamp wattage	5 W
[Ue] rated operational voltage	24/48 V DC
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	470 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Metal parts Cross rails
Fixing mode	Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Length	310 mm
Height	30.5 mm
Colour	Aluminium

## Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-16...65 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.9 cm
Package 1 Width	5.4 cm
Package 1 Length	35.0 cm
Package 1 Weight	200.0 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Recommended replacement(s)