



Notes:

- Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25° C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40° C to +85° C
- Material and Finish:
 - ⓐ - Receptacle Housing: Zinc Die-Cast, Nickel Plated
 - Panel Nut: Brass, Nickel Plated
 - Panel Gasket: Silicon, Color: White
 - RJ45 PCB Jack Metal Shell: Copper Alloy, Nickel Plated
 - RJ45 PCB Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - RJ45 PCB Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- IP67 rated when fully mated with appropriate mating connector

Description	Part Number
Metal Version with Shielded RJ45 PCB Jack	17-101594
Potted Metal Version with Shielded RJ45 PCB Jack	17-101634

RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm
	Name	Title	Approval Date	0 PLC ± 0.50	1 PLC ± 0.38		Autodesk Inventor	Material: See Notes
	1 x e	Ä21-0426	02.11.2021	Bub	2 PLC ± 0.25	2009 Date	Name	Title: Receptacle Assembly Kit
	d	1	Jan/12/12	Vincent Ke	3 PLC ± 0.10	Draw. Jun. 03	Vincent Ke	with Shielded Cat. 5e RJ45 PCB Jack
	c	2	Mar/08/11	Vincent Ke	ANGLES ± 3°	Appd. Jun. 03	J. Chaudry	M28 Metal Version
b	1	Aug/26/09	Vincent Ke		Norm		Drawing No.: 17K1A248	DIN A3
a	original				D-old		Part No.: SEE P/N TABLE	Sheet 1/1
Rev	Changes	Date	Name					