

# Lineman's Pliers

DIN ISO 5746 ASME B107.20

09

High transmission ratio for easy cutting.

High leverage design requires 50% less effort compared to conventional combination pliers due to an optimized transmission ratio.

- > heavy-duty
- > ergonomically optimized handle shape for firm contact to the hand and fatigue reducing operation
- > effective cross-hatched knurled gripping zone in the jaws – for strong gripping and pulling
- > serrated gripping zone below the joint for powerful leverage
- > cutting edges for soft and hard wire, nails, ACSR and piano wire
- > cutting edge hardness (approx. 64 HRC)
- > vanadium steel, forged, multi stage oil-hardened

### 09 11 240 / 09 12 240 / 09 12 240 T BKA\*

With fish tape puller in the joint gap; with universal crimping point below the joint

### 09 02 240 T BKA / 09 12 240 T BKA\*

Pliers with integrated tether attachment point for tool drop protection system



Gripping zone below the joint for powerful leverage



09 01 240



09 02 240



09 02 240 T BKA



09 08 240 US



09 11 240



09 12 240 T BKA





09 11/12 240:  
Universal crimping area below the joint


























09 11/12 240:  
Fish tape puller in the joint gap



Cross-hatched, knurled gripping zone for firm gripping and pulling, e. g. for fence construction



Long cutting edges for cutting flat cables

Product Number	Packaging	↔ Inch mm	 	Pliers	Head	Handles	Cutting capacities		 lbs
							 Ø Inch Ø mm	 Ø Inch Ø mm	
09 01 240	X	9 1/2 240	 	black atramentized	polished	plastic coated	3/16 4.6	1/8 3.0	0.96
09 02 240	X	9 1/2 240	 	black atramentized	polished	multi-component grips	3/16 4.6	1/8 3.0	1.01
09 02 240 T BKA	X	9 1/2 240	 	black atramentized	polished	multi-component grips, integrated tether attachment point	3/16 4.6	1/8 3.0	1.08
09 08 240 US	X	9 1/2 240	 1000 V ASTM  	black atramentized	polished	insulated, multi-component handles, ASTM-tested	3/16 4.6	1/8 3.0	1.02
09 11 240	X	9 1/2 240	  	black atramentized	polished	plastic coated	3/16 4.6	1/8 3.0	0.91
09 12 240	X	9 1/2 240	  	black atramentized	polished	multi-component grips	3/16 4.6	1/8 3.0	1.04
09 12 240 T BKA	X	9 1/2 240	  	black atramentized	polished	multi-component grips, integrated tether attachment point	3/16 4.6	1/8 3.0	1.07

