

## Han 64EEE panel feed through



Image is for illustration purposes only. Please refer to product description.

Part number	09 32 064 0001
Specification	Han 64EEE panel feed through
HARTING eCatalogue	<a href="https://b2b.harting.com/09320640001">https://b2b.harting.com/09320640001</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> EEE
Element	Panel feed through

### Version

Termination method	Crimp termination
Gender	Male Female
Size	24 B
Number of contacts	64
PE contact	Yes

### Technical characteristics

Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$

### Material properties

Material (insert)	Polycarbonate (PC)
-------------------	--------------------



Pushing Performance  
Since 1945

## Material properties

Colour (insert)	RAL 7032 (pebble grey)
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

## Commercial data

Packaging size	1
Net weight	258 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140049420
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors