

### product type designation



### M826-2 SHDSL

SCALANCE M826-2 SHDSL router; for the IP communication via 2-wire and 4-wire cables from Ethernet-based Programmable controllers; SHDSL topology: Point-to-point, bonding, line bridge mode; Routing mode with VPN, Firewall, NAT; 4-port switch; 1x digital input, 1x digital output .

transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
transfer rate	
<ul style="list-style-type: none"> <li>for SHDSL transmission / maximum</li> </ul>	15.3 Mbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> <li>for internal network</li> </ul>	4
<ul style="list-style-type: none"> <li>for external network</li> </ul>	2
number of electrical connections	
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	2
type of electrical connection	
<ul style="list-style-type: none"> <li>for internal network</li> </ul>	RJ45 port (10/100 Mbit/s, TP, autocrossover)
<ul style="list-style-type: none"> <li>for external network</li> </ul>	Terminal strip
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	Terminal strip
WAN connection	
type of WAN connection / is supported / SHDSL	Yes
supply voltage, current consumption, power loss	
supply voltage / rated value	24 V
supply voltage / rated value	10.8 ... 28.8
type of voltage / of the supply voltage	DC
consumed current	
<ul style="list-style-type: none"> <li>at rated supply voltage / maximum</li> </ul>	290 mA
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +80 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
depth	127 mm
height	147 mm
width	35 mm
fastening method	
<ul style="list-style-type: none"> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>S7-300 rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>S7-1500 rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>wall mounting</li> </ul>	Yes

product features, product functions, product components / general	
product function	
• DynDNS client	Yes
• no-ip.com client	Yes
product functions / management, configuration, engineering	
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
type of configuration	Web-based management
product functions / diagnostics	
protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v2c	Yes
• SNMP v3	Yes
product function	
• statistics Packet Size	No
• statistics packet type	No
• error statistics	No
• SysLog	Yes
• packet filter log	Yes
product functions / DHCP	
product function	
• DHCP client	Yes
• DHCP server - internal network	Yes
product functions / routing	
router function	
• NAT (IP masquerading)	Yes
• port forwarding	Yes
• NAT traversal	Yes
• 1:1 NAT	Yes
• DNS cache	Yes
product functions / security	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
• password protection	Yes
• packet filter	Yes
• broadcast/multicast/unicast limiter	No
product function	
• broadcast blocking	No
• with VPN connection	IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK	Yes
protocol / is supported	
• IPsec tunnel and transport mode	Yes
key length	
• 1 / with IPsec AES / with Virtual Private Network	128 bit
• 2 / with IPsec AES / with Virtual Private Network	192 bit
• 3 / with IPsec AES / with Virtual Private Network	256 bit
• with IPsec 3DES / with Virtual Private Network	168 bit
type of Internet key exchange / with Virtual Private Network	

<ul style="list-style-type: none"> <li>main mode</li> <li>quick mode</li> </ul>	<p>Yes</p> <p>Yes</p>
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
<b>product functions / time</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>NTP</li> <li>SNTP</li> </ul>	<p>Yes</p> <p>Yes</p>
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>for FM</li> <li>for hazardous zone</li> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> </ul>	<p>FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4</p> <p>EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X</p> <p>UL E115352 Vol. X2</p> <p>ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC</p>
certificate of suitability	
<ul style="list-style-type: none"> <li>CE marking</li> <li>CCC approval</li> <li>railway application in accordance with EN 50121-3-2</li> <li>railway application in accordance with EN 50121-4</li> <li>railway application in accordance with EN 50155</li> <li>railway application in accordance with EN 61373</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; no coated printed circuit boards</p> <p>Yes; cat. 1, cl.A and cl. B</p>
Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> <li>French marine classification society (BV)</li> <li>DNV GL</li> <li>Korean Register of Shipping (KRS)</li> <li>Lloyds Register of Shipping (LRS)</li> <li>Nippon Kaiji Kyokai (NK)</li> <li>Polski Rejestr Statkow (PRS)</li> <li>Royal Institution of Naval Architects (RINA)</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Selection guide for cables and connectors</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<p><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></p> <p><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></p> <p><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></p> <p><a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a></p> <p><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></p> <p><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>
<b>security information</b>	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>
last modified:	4/29/2021 