



71624-3001	WITH M-3 THREADED INSERT
71624-3000	WITHOUT M-3 THREADED INSERT
ITEM NUMBER	DESCRIPTION

**NOTES**

- MATERIALS:**  
INSULATOR: GLASS FILLED LCP, 94V-0, COLOR BLACK.  
SHIELD: DEEP DRAW STEEL, .020" THICK.
- PLATING: 100 MICRO-INCHES MINIMUM BRIGHT NICKEL OVER COPPER UNDERPLATE OVERALL.
- CONFORMS TO PRODUCT SPECIFICATION PS-71626.
- CONFORMS TO APPLICATION SPECIFICATION PS-71624.
- INSERT MOLDED CONTACT STRIPS ARE SUPPLIED SEPARATELY, SEE SALES DRAWING\* SDA-70984-4\*\*\* FOR ORDER NUMBERS.
- BULK PACKAGING: 100 SUB-ASSEMBLIES PER CARTON

<b>REVISION NOTE 2</b> EC NO: UCP2016-0871 DRW: SVANG01 2015/08/26 CHK: DMORGAN 2015/08/26 APPR: SMILLER 2015/09/10	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	▽=0	mm INCH	IN/MM	4:1	INCH	☉
	▽=0	4 PLACES ± --- ± ---	DRAWN BY DATE	TITLE		
	▽=0	3 PLACES ± --- ± ---	CHECKED BY DATE	160 CKT LFH I/O PLUG HSG/SHLD SUB. ASSY. FOR CABLE APPLICATION <b>molex</b>		
	▽=0	2 PLACES ± --- ± ---	APPROVED BY DATE			
	1 PLACE ± --- ± ---	MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
	0 PLACE ± --- ± ---	SEE TABLE		SDA-71624-3000		1 OF 1

ANGULAR ±1/2°  
 DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SIZE C THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION