




ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00604	Connector, 3 pin M5 socket, 5xL14.5mm, gold plated, molding style, solder cup, IP67	2	
2	30-00653	Wire, 2C TS, 28 AWG, 150V, 70C, 2.6 mm, spiral shield, TPU, WBL	1	
3	24-00263	Overmold, M5, 6xL22 mm	2	TPU, black



Front View  
Not to Scale



Front View  
Not to Scale

**Notes:**  
Functionally equivalent components may be substituted

IP67 waterproof rating when mated with corresponding (IP67) connector

Cable rated for 60 V, 1.0 A

Wiring Diagram		
50-00604	wire color	50-00604
1	white	1
3	black	3
4	shield	4

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	04/02/2018	Initial release	JC <small>Digitally signed by JC Date: 2020.03.19 17:09:29 -07'00'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	Size: Part number: A 10-03010
			AG <small>Digitally signed by AG Date: 2020.03.20 09:42:20 -07'00'</small>	Description:	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5x0.5 mm 3C 50-00604 M5 socket to same, 28 AWG, 30-00653 wire, IP67	Scale: 1:1

5

4

3

2

1



Sheet 1 of 1