

Reducing bridge - RB PTPOWER 35-ST 16 - 3032170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing bridge, for bridging of PTPOWER 35 to ST or PT ..N terminal blocks with 16 mm² nominal cross section, Pitch: 14.5 mm, Length: 5 mm, Width: 22.9 mm, Number of positions: 2, Color: red

The figure shows a similar product



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85389099
Country of origin	Poland

Technical data

Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	--

Technical data

Color	red
Material	PA 6.6
Number of positions	2
Pitch	14.5 mm
Maximum load current	90 A
Flammability rating according to UL 94	V0

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Reducing bridge - RB PTPOWER 35-ST 16 - 3032170

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426