



Load disconnecter 3LD3, Iu 63 A Main switch 3-pole + N Rated operating capacity at AC-23 A at 400V 22.0 kW floor mounting Basic switch with door coupling Central hole mounting 22.5mm Rotary actuator red / yellow 66 x 66 mm with auxiliary switch 1OE + 1S

| Model   |  |
|---|--|
| product brand name  | SENTRON                                |
| product designation   | 3LD Switch disconnecter                |
| design of the product   | EMERGENCY-STOP switch                  |
| display version / for switch position indicator manual operation  | 1 ON - 0 OFF                           |
| design of the actuating element   | Short rotary knob                      |
| design of handle  | rotary operating mechanism, red/yellow |
| type of the driving mechanism / motor drive   | No                                     |
| General technical data  |  |
| number of poles   | 4                                      |
| number of poles / note  | 4                                      |
| type of device  | fixed mounting                         |
| type of switch  | Floor mounting with door coupling      |
| mechanical service life (switching cycles) / typical  | 100 000                                |
| electrical endurance (switching cycles)   |  |
| • at AC-23 A / at 690 V   | 6 000                                  |
| I <sup>2</sup> t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum             | 21 kA <sup>2</sup> .s                  |
| let-through I <sup>2</sup> t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum | 21 kA <sup>2</sup> .s                  |
| operating frequency / maximum   | 50 1/h                                 |
| Voltage   |  |
| insulation voltage / rated value  | 690 V                                  |
| surge voltage resistance / rated value  | 6 kV                                   |
| Protection class  |  |
| protection class IP   | IP65                                   |
| degree of protection NEMA rating  | 1, 3R, 4X, 12                          |
| protection class IP / on the front  | IP65                                   |
| Dissipation   |  |
| power loss [W]  |  |
| • for rated value of the current / at AC / in hot operating state / per pole                                    | 4.5 W                                  |
| • per conductor / typical   | 5 W                                    |
| Current   |  |
| operational current   |  |
| • at 40 °C / rated value  | 63 A                                   |
| • at 45 °C / rated value  | 63 A                                   |
| • at 50 °C / rated value  | 63 A                                   |
| • at 55 °C / rated value  | 63 A                                   |

|   |                                |
|---|--------------------------------|
| <ul style="list-style-type: none"> <li>• at AC / rated value</li> </ul>   | 63 A                           |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 400 V / rated value</li> </ul>                               | 43 A                           |
| <ul style="list-style-type: none"> <li>• at AC-21 / at 690 V / rated value</li> </ul>                                 | 63 A                           |
| <ul style="list-style-type: none"> <li>• at AC-21 A / at 240 V / rated value</li> </ul>                               | 63 A                           |
| <ul style="list-style-type: none"> <li>• at AC-21 A / at 440 V / rated value</li> </ul>                               | 63 A                           |
| operational current / of upstream fuse / rated value  | 63 A                           |
| let-through current / with closed switch  |                                |
| <ul style="list-style-type: none"> <li>• at 440 V / for combination switch + gG fuse / maximum</li> </ul>             | 6 kA                           |
| <ul style="list-style-type: none"> <li>• at 690 V / for combination switch + gG fuse / maximum permissible</li> </ul> | 6 kA                           |
| <b>Main circuit</b>   |                                |
| operating power   |                                |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 240 V / rated value</li> </ul>                               | 11 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 400 V / rated value</li> </ul>                               | 22 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 440 V / rated value</li> </ul>                               | 22 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 690 V / rated value</li> </ul>                               | 19 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 240 V / rated value</li> </ul>                                  | 11 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 400 V / rated value</li> </ul>                                  | 19 kW                          |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 690 V / rated value</li> </ul>                                  | 15 kW                          |
| operational current / rated value   | 63 A                           |
| <b>Auxiliary circuit</b>  |                                |
| number of CO contacts / for auxiliary contacts  | 0                              |
| number of NC contacts / for auxiliary contacts  | 1                              |
| number of NO contacts / for auxiliary contacts  | 1                              |
| operating voltage / of auxiliary contacts / at AC / maximum   | 500 V                          |
| continuous current / of the auxiliary contact / rated value   | 10 A                           |
| insulation voltage / of the auxiliary switch / rated value  | 500 V                          |
| <b>Suitability</b>  |                                |
| suitability for use   |                                |
| <ul style="list-style-type: none"> <li>• main switch</li> </ul>   | Yes                            |
| <ul style="list-style-type: none"> <li>• switch disconnecter</li> </ul>   | Yes                            |
| <ul style="list-style-type: none"> <li>• EMERGENCY OFF switch</li> </ul>  | Yes                            |
| <ul style="list-style-type: none"> <li>• safety switch</li> </ul>   | Yes                            |
| <ul style="list-style-type: none"> <li>• maintenance/repair switch</li> </ul>   | Yes                            |
| <b>Appearance</b>   |                                |
| color / of the actuating element  | red                            |
| <b>Product details</b>  |                                |
| product feature   |                                |
| <ul style="list-style-type: none"> <li>• can be locked into OFF position</li> </ul>                                   | Yes                            |
| number of bracket locks / maximum   | 2                              |
| hasp thickness / of the bracket locks / minimum   | 4 mm                           |
| hasp thickness / of the bracket locks / maximum   | 6 mm                           |
| special product feature   | Can be locked in zero position |
| product extension / optional  |                                |
| <ul style="list-style-type: none"> <li>• motor drive</li> </ul>   | No                             |
| <ul style="list-style-type: none"> <li>• voltage trigger</li> </ul>   | No                             |
| <b>Short circuit</b>  |                                |
| conditional short-circuit current / with line-side fuse protection  |                                |
| <ul style="list-style-type: none"> <li>• at 440 V / by gG fuse / rated value</li> </ul>                               | 10 kA                          |
| <ul style="list-style-type: none"> <li>• at 690 V / by gG fuse / rated value</li> </ul>                               | 6 kA                           |
| <b>according UL</b>   |                                |
| operational current / at AC / according to UL 508/UL 60947-4-1 / rated value  | 63 A                           |
| operating voltage / at AC / at 50/60 Hz / according to UL 508/UL 60947-4-1 / rated value                              | 600 V                          |
| active power [hp] / at AC / at 480 V / according to UL 508/UL 60947-4-1 / rated value                                 | 25                             |
| active power [hp] / at AC / at 600 V / according to UL 508/UL 60947-4-1 / rated value                                 | 30                             |

|   |  |
|---|--|
| short-time withstand current (SCCR) / at 600 V / according to UL 508/UL 60947-4-1 | 5 kA   |
| continuous current / of upstream fuse / according to UL / rated value             | 50 A   |
| type of fuse / according to UL  | RK5  |
| <b>Number</b>   |  |
| number of connectable NC contacts / for auxiliary contacts / attachable / maximum | 2  |
| number of connectable NO contacts / for auxiliary contacts / attachable / maximum | 4  |
| number of connectable CO contacts / for auxiliary contacts / attachable / maximum | 0  |
| <b>Connections</b>  |  |
| AWG number / as coded connectable conductor cross section / solid                 |  |
| • maximum   | 6  |
| • minimum   | 14   |
| type of connectable conductor cross-sections / for copper conductor               |  |
| • solid   | 1x (2.5 to 16 mm <sup>2</sup> )                            |
| • finely stranded / with core end processing                                      | 1x (2.5...16 mm <sup>2</sup> )                             |
| • stranded  | 1x (2.5 to 16 mm <sup>2</sup> )                            |
| type of connectable conductor cross-sections / for auxiliary contacts             |  |
| • solid   | 2x (0.75 ... 2.5 mm <sup>2</sup> ), 1x 4 mm <sup>2</sup>   |
| • finely stranded / with core end processing                                      | 2x (0.75 ... 1.5 mm <sup>2</sup> ), 1x 2.5 mm <sup>2</sup> |
| • stranded  | 2x (0.75 ... 2.5 mm <sup>2</sup> ), 1x 4 mm <sup>2</sup>   |
| type of electrical connection   |  |
| • for main current circuit  | box terminal   |
| • for auxiliary contacts  | Box terminals  |
| <b>Requirements</b>   |  |
| design of the fuse link   |  |
| • for short-circuit protection of the main circuit / required                     | fuse gL/gG: 63 A   |
| • for short-circuit protection of the auxiliary switch / required                 | fuse gL/gG: 10 A   |
| <b>Mechanical Design</b>  |  |
| height  | 60 mm  |
| width   | 60 mm  |
| depth   | 380 mm   |
| fastening method  | Built-in unit fixed-mounted version                        |
| fastening method  |  |
| • 4-hole front mounting   | No   |
| • front mounting with central attachment  | Yes  |
| • rail mounting   | Yes  |
| net weight  | 300 g  |
| <b>Environmental conditions</b>   |  |
| ambient temperature / during operation  |  |
| • minimum   | -25 °C   |
| • maximum   | 55 °C  |
| ambient temperature / during storage / minimum                                    | -25 °C   |

**General Product Approval**

**Declaration of Conformity**

[Confirmation](#)



other

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3LD3448-1TL53>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3LD3448-1TL53>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3LD3448-1TL53](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3LD3448-1TL53)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



