



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 457-2

Documents

Panel piercing B 98

Material and plating

Connector parts

- Center contact
- Outer contact
- Body
- Coupling nut
- Dielectric 1
- Dielectric 2

Material

- CuBe
- CuBe
- Stainless steel
- Stainless steel
- PPE
- PTFE

Plating

- Gold, min. 1.27 µm, over chemical nickel
- Gold, min. 1.27 µm, over chemical nickel
- Passivated
- Passivated

Electrical data

Impedance	50 Ω
Frequency	DC to 18 GHz
Return loss	≥ 26 dB, DC to 18 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage (at sea level)	1000 V rms
Working voltage (at sea level)	480 V rms
RF-leakage	≥ 120 dB up to 1 GHz

Mechanical data

Mating cycles	≥ 5000
Center contact captivation	≥ 28 N
Coupling test torque	1.95 Nm
Recommended torque	1.36 Nm

Environmental data

Temperature range	-40°C to +85°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Weight

50.3 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
H. Babinger	09.08.04	F. Reiner	10.07.18	b01	18-1026	M. Ruf	06.07.18