

## Panel feed-through - Q 1,5/4A10/24-M20KU-ESA BK PE - 1584787

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Panel feed-through with wire exit 1.5 mm<sup>2</sup> and 0.1 m litz wire: connecting thread: M20, 4-pos.

### Product Features

- ✓ Innovative and time saving - QUICKON fast connection for time saving of up to 80% for on-site connection
- ✓ Convenient: quick and easy assembly without special tools
- ✓ Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- ✓ Safer connection thanks to polarization against mismatching and touch-proof protection according to DIN EN 0105
- ✓ Efficient - by using panel feed-throughs, devices no longer need to be opened in order to connect cables



### Key commercial data

Packing unit	1 PCE
Custom tariff number	85444290
Country of origin	Poland

### Technical data

#### General

Connection	If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Length of cable	0.1 m
Color	black
Connection method	QUICKON connection
	Single litz wires 10 cm long; 1.5 mm <sup>2</sup>
Note on the internal connection type	Pos. 1: black; pos. 2: brown; pos. 3: blue; pos. 4: green/yellow
Number of positions	4
Wrench size, union nut	19 mm
Tightening torque, union nut	3 Nm
Wrench size, contact carrier	24 mm

# Panel feed-through - Q 1,5/4A10/24-M20KU-ESA BK PE - 1584787

## Technical data

### General

Tightening torque contact carrier	4.5 Nm
Tightening torque, counter nut	4.5 Nm
Number of connections	4
Conductor cross section stranded min.	0.75 mm <sup>2</sup>
Conductor cross section stranded max.	1.5 mm <sup>2</sup>
Conductor cross section solid min.	0.75 mm <sup>2</sup>
Conductor cross section solid max.	1 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	18
Conductor cross section AWG/kcmil max	16

### Conductor

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6 / min. 0.15 mm
Wire insulation material	PVC/PE
Wire diameter including insulation	>= 1.8 mm ... 3 mm
External cable diameter	6 mm ... 12 mm

### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-40 °C ... 80 °C (specifications of the cable manufacturer must also be observed)
	-25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.)
Temperature when conductor connected	-5 °C ... 50 °C (specifications of the cable manufacturer must also be observed)

### Electrical characteristics

Nominal current I <sub>N</sub>	17.5 A
Rated current	15 A
Rated voltage (III/3)	500 V
Note on the rated voltage (III/3)	with insulating sleeve PT/FS 4,8. Without insulating sleeve 250 V AC.
Rated voltage (III/2)	800 V
Note on the rated voltage (III/2)	with insulating sleeve
Rated voltage (II/2)	1000 V
Note on the rated voltage (II/2)	with insulating sleeve
Rated surge voltage (III/3)	6 kV
Rated surge voltage (III/2)	6 kV
Rated surge voltage (II/2)	6 kV

### Mechanical characteristics

# Panel feed-through - Q 1,5/4A10/24-M20KU-ESA BK PE - 1584787

## Technical data

### Mechanical characteristics

QUICKON connectability	max. 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)
PC QUICKON thread type	M20
Impact category	3

### Material data

Contact material	CuZn
Contact surface material	Tin-plated
Contact carrier material	PA
Insulating material	PA
Inflammability class according to UL 94	V0
Surge voltage category	III
Pollution degree	3

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440312

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002641
ETIM 5.0	EC002641

### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

# Panel feed-through - Q 1,5/4A10/24-M20KU-ESA BK PE - 1584787

## Approvals

Approvals

---

Approvals

VDE Zeichengenehmigung

---


Ex Approvals

---

Approvals submitted

---

## Approval details

VDE Zeichengenehmigung 	
mm <sup>2</sup> /AWG/kcmil	0.75-1.5
Nominal voltage UN	500 V

## Accessories

Accessories

Insulating sleeve

Insulating sleeve - PT/FS 4,8 - 1670497



Insulating sleeve, as touch protection, for 4.8 mm slip-on sleeves, slide onto the conductor before

---

Mounting material

# Panel feed-through - Q 1,5/4A10/24-M20KU-ESA BK PE - 1584787

## Accessories

Nut - Q-MU M20 - 1640702



Nut (plastic) to lock the contact carrier from the inside of the device

## Protective cap

Filler plugs - Q-PROT13/16 - 1670222



Closing caps, for Pg13/ Pg16, for closing unoccupied connections

## Socket spanner


Socket wrench - QSS 19 - 1670895



Socket wrench, for tightening and unscrewing the QUICKON union nut, wrench size 19 mm

## Drawings

Diagram



Dimensioned drawing

