3M[™] Reusable Respirators

Contort rust Contort rust Espirators for Your Workplace





3M[™] Ultimate FX Full Facepiece Reusable Respirator FF-400 Series

Comfortable, durable protection for demanding, X-treme conditions

The lightweight Ultimate FX FF-400 was developed to provide maximum comfort and durability with unique features that make it the optimal choice for a variety of industrial applications:



3M[™] Full Facepiece Reusable Respirator 6000 Series

Reliable, convenient, compatible protection


- Unique center adapter directs exhaled breath and moisture downward, and helps reduce debris from depositing in the valve. Smooth surface allows for quick and easy cleaning
- Large lens provides wide field of view and excellent visibility
- 3M[™] Cool Flow[™] Valve helps provide cool, dry comfort
- Meets requirements of ANSI Z87.1-2010 for high impact (Z87+)
- Lightweight, well-balanced design with silicone faceseal for enhanced comfort and durability
- Available in air purifying respirator (APR), supplied air and powered air purifying respirator (PAPR) modes

6700 (Small) 6800 (Medium) 6900 (Large)



3M[™] Full Facepiece Reusable Respirator 7800S Series

7800S-S (Small) 7800S-M (Medium) 7800S-L (Large)



- Silicone facepiece enhances fit and improves durability
- Double-flange faceseal and six adjustable straps help provide a secure fit
- Can be used with a passive or electronic clip-on welding lens
- Available in air purifying respirator (APR), supplied air and powered air purifying respirator (PAPR) modes
- FR-7800B (First Responder) version available
 - Butyl rubber seal to minimize permeation
 - CBRN approved with FR-15-CBRN





3M[™] Half Facepiece Reusable Respirator 7500 Series

Easy breathing, comfort and durability

7501 (Small) 7502 (Medium) 7503 (Large)

Soft Seal Design

- Advanced silicone material provides a softer feel on the face
- Unique adjustment design helps reduce tension and pressure points on the face for unsurpassed comfort

Cool Flow[™] Valve

breathing easier

Valve design helps make

Helps reduce heat and

moisture buildup for

cool, dry comfort

Adjustable Head Cradle

 Allows wearer to adjust for optimum fit and comfort

Dual-mode Head Harness

 Adjusts easily so user has the option of wearing respirator in either traditional or drop-down mode

Unique Exhalation Valve Cover

- Directs exhaled breath and moisture downward
- Smooth surface allows for quick and easy cleaning
- Helps reduce debris from depositing in valve area

3M[™] Rugged Comfort Half Facepiece Reusable Respirator 6500 Series

Rugged comfort, durability, and slim profile design

Adjustable Head Harness Assembly

- Optimum fit and comfort with threesize adjustable head cradle
- Long-lasting polyester/spandex straps

3M[™] Bayonet Connection

 Compatible with all 3M[™] bayonet-style cartridges and filters

Quick Latch Drop-Down Mechanism*

- Easy on and off as you move in and out of contaminated areas
- No need to remove your hard hat or faceshield when lowering or raising your respirator
- *Available on models 6501QL, 6502QL and 6503QL.

Valve Cover Design

- Directs exhaled breath and moisture downward
- Easy positive pressure seal check

6501 (Small)

6503 (Large)

6502 (Medium)

6501QL (Small)

6503QL (Large)

6502QL (Medium)

with a soft but firm faceseal

Silicone Faceseal

• Extended product life due to resilient silicone material

· Provides comfort and stability

- Our lightest silicone facepiece
- Keeps its shape in high-heat environments

Cool Flow[™] Valve

- Enhanced comfort by reducing heat and moisture
- Easier breathing with unique valve design

4

3M[™] Half Facepiece Reusable Respirator 6000 Series

Compatible, convenient respiratory protection

- Facepiece is made from soft, lightweight material
- Available with a standard or drop-down head harness option. Drop-down model allows wearers to lower the respirator without removing hard hat or faceshield
- Head harness assembly and spare parts are available



Standard

6100 (Small) 6200 (Medium) 6300 (Large)



Drop-down

6100DD (Small) 6200DD (Medium) 6300DD (Large)



3M[™] Half Facepiece Disposable Respirator 5000 Series

Balanced design, disposable convenience

- Easy to use and convenient
- Pre-assembled with permanently attached cartridges; no maintenance necessary
- Facepiece is made from soft, lightweight material
- Ideally suited for:
 - Intermittent respirator use
 - Plant shutdowns and turnarounds
 - Dirty applications where respirators wear out or become difficult to clean in a short time

5101 Organic Vapor Respirator (Small) 5201 Organic Vapor Respirator (Medium) 5301 Organic Vapor Respirator (Large) 5103 Organic Vapor/Acid Gas Respirator (Small) 5203 Organic Vapor/Acid Gas Respirator (Medium) 5303 Organic Vapor/Acid Gas Respirator (Large) 51P71 P95 Paint Spray/Pesticide Assembly (Small) 52P71 P95 Paint Spray/Pesticide Assembly (Medium) 53P71 P95 Paint Spray/Pesticide Assembly (Large)





Identify the Hazards

Applications and Industries	Potential Hazards	Cartridge/Filter Options*		
Spray Painting, Varnishing, Staining & Coating	Solvent-based	OV/P95		
	Water-based Latex	Nuisance OV**/P95		
Sanding & Grinding	Particulate	N95		
Welding	Weld Fume	N95		
	Stainless Steel & Galvanized	Nuisance OV**/P95		
Abatement	Lead & Asbestos	P100		
	Mold	N95 - P100/ Nuisance OV**		
Cement Work	Silica/Dust	N95		
Cleaning & Janitorial	Bleach	AG/P95		
	Ammonia	AM/MA/P95		
	General Cleaning Products	OV/P95		
Agriculture	Pesticides & Insecticides	0V/AG/P95 - P100		
Construction	Particulate	N95		
Manufacturing	Solvents	OV		
	Particulate	N95		
Pharmaceutical Manufacturing	Particulate	N95/P100		
Chemical Manufacturing	Sulfur Dioxide, Chlorine	AG/P95		
	Ammonia	AM/MA/P95		

*Respirator facepiece or system must be chosen based on the contaminant, airborne concentration and the necessary assigned protection factor.

**Nuisance level refers to concentrations below the Occupational Exposure Limit (OEL) or other applicable government regulations, whichever is lower. If you are uncertain of the concentration levels of contaminants or recommended levels of respiratory protection, contact the 3M Technical Service Helpline at 1-800-243-4630. This guide is only an outline. It should not be used as the only means for selecting a respirator. Details regarding performance and limitations are set out on the respirator package and *User Instructions*. Before using any of these respirators, the wearer must read and understand the User Instructions for each product.

RA

	52	10	AR	A			A
Select the Right Respirator	5000	6000 HF	6500	7500	6000 FF	FF-400	7800S
Enhanced Durability							•
Maintenance Free							
Enhanced Comfort			•				
Drop-down Feature		*	**				
3M [™] Cool Flow [™] Valve			•				
Compatible with $\mathrm{3M}^{\mathrm{\tiny M}}$ Supplied Air System							•
Compatible with 3M [™] PAPR Systems					•		•
Eye Protection					•		•
Speaking Diaphragm							•
Accessories					•		•
Spare Parts			•				•
Six-point Head Harness							•
Silicone Faceseal			•				•
Compatible with Welding Shield							
Clip-on Welding Shield							

*6000DD Version.

**6500QL Version.

Find a Combination that Works Best for You







6500 Series



7500 Series



6000 Series



Ultimate FX FF-400



7800 Series



7

3M[™] Particulate Filters and Gas/Vapor Cartridges

All 3M Particulate Filters and Gas/Vapor Cartridges can be used interchangeably with 3M[™] Reusable Respirators 6000, 6500, 7000 and FF-400 Series.

3M [™] Particulate Filters 2000 Series							
		Part Number	Description				
alles Com Com	 Lightweight and easy to breathe through 	2071	Particulate Filter, P95				
	Assortment of filters available	2076HF	F Particulate Filter, Hydrogen Fluoride/P95, with Nuisance Level Acid Gas Reli				
	for a wide range of applications	2078 Particulate Filter, P95, with Nuisance Level Organic Vapor/Acid Gas Re					
alle alle alle	Easier breathing through new 3-layer advanced Electret Filter	2091	Particulate Filter, P100				
	Media in 2200 Series Filters	2096 Particulate Filter, P100, with Nuisance Level Acid Gas Relief*					
		2097	Particulate Filter, P100, with Nuisance Level Organic Vapor Relief*				
		2291	Advanced Particulate Filter, P100				
		2296	Advanced Particulate Filter, P100, with Nuisance Level Acid Gas Relief*				
		2297	Advanced Particulate Filter, P100, with Nuisance Level Organic Vapor Relief*				
3M [™] Particulate Filter 709	93, P100						
• Unique, spring-loaded filter cover d	esign	7093	Particulate Filter, P100				
simplifies negative pressure user se	eal checks	7093B					
 Swept-back design provides enhanted areater comfort 	 Swept-back design provides enhanced field of view and greater comfort 7093C offers a lightweight, low profile design 		Particulate Filter, P100, Bulk				
			On this to the last one Florida Droop 11 Million in the				
that combines P100 filtration with c	carbon-loaded	7093C	Cartridge/Filter, Hydrogen Fluoride, P100 with Nuisance Level Organic Vapor and Acid Gas Relief*				
features found in heavier combinati	on cartridge products						
3M [™] Gas/Vapor Cartridges	s 6000 Series						
		6001	Cartridge, Organic Vapor				
	 Low-profile design helps maintain good field of vision 	6002	Cartridge, Acid Gas**				
	Full range of cartridges to meet	6003	Cartridge, Organic Vapor/Acid Gas**				
	your needs	6004	Cartridge, Ammonia/Methylamine				
		6005	Cartridge, Formaldehyde/Organic Vapor				
Contraction of the second		6006	Cartridge, Multi Gas/Vapor**				
		6009	Cartridge, Mercury Vapor or Chlorine				
3M [™] Combination Cartridg	ges/P100 Particulate Filters 6000	0 Series					
	 Particulate filter is permanently attached to cartridge for easy, one-step assembly Unique design for enhanced comfort and visibility 	60921 📉	Cartridge/Filter, Organic Vapor/P100				
		60922 📃	Cartridge/Filter, Acid Gas/P100**				
		60923 📉	Cartridge/Filter, Organic Vapor/Acid Gas/P100**				
		60924 📉	Cartridge/Filter, Ammonia/Methylamine/P100				
	·····	60925	Cartridge/Filter, Formaldehyde/Organic Vapor/P100				
		60926	Cartridge/Filter, Multi-Gas/Vapor/P100**				
3		60928	Cartridge/Filter, Organic Vapor/Acid Gas/P100**†				
		60929	Cartridge/Filter, Mercury Vapor/Chlorine Gas/P100				
	* 3M recommended for relief against nuisance levels of organic vapors and acid gases. Nuisance level organic vapor and acid gas refers to concentrations not exceeding OSHA PEL						
			Do not use for respiratory protection against acid gases or organic vapors (except hydrogen fluoride). hydrogen sulfide gas up to 10 times the permissible exposure limit (PEL) with half facepiece respirators				
	and full facepiece respirators when qualitatively fi	it tested, or up to less th	an 300 parts per million (ppm) with full facepiece respirators when quantitatively fit tested or ons, whichever is lower. 300 ppm is the concentration considered Immediately Dangerous to Life or				
	Health (IDLH) for hydrogen sulfide.	0 0					
For More Information	[†] As recommended by the California Department of methylbromide. Note: not NIOSH approved for me		 D1-009-Methyl Bromide Field Fumigation. 3M recommended for use against radioiodine and ne. 				
In the United States, contact:							
Technical Service	Customer Service	Internet					
1-800-243-4630	1-800-328-1667	www.3M.com/	PPESatety				
In Canada, contact:							
Technical Service 1-800-267-4414	3M Canada Customer Care 1-800-364-3577	Internet www.3M.ca/safety					
For other 3M products:							
Technical Service 1-800-3M-HELPS		These respirators help protect against certain airborne contaminants. Misuse may result in sickness or death.					
	3M, Scotchgard and Cool Flow	For proper use, the wearer must read and understand User rovided as a part of product packaging, see supervisor, or call 3M PSD Technical Service,					
3 M	are trademarks of 3M Company,		630. Time use limitations may apply.				



Personal Safety Division 3M Center, Building 235-2W-70 St. Paul, MN 55144-1000

are trademarks of 3M Company, used under license in Canada. Please recycle. Printed in U.S.A. © 2013 3M Company. All Rights Reserved. 70-0710-9082-6

1-600-243-4630. Time use imitations may apply.
Important — Before using these respirators, you must determine the following:
1. The type of contaminant(s) for which the respirator is being selected.
2. The concentration level of contaminant(s).
3. Whether the respirator can be properly fitted on the wearer's face. All respirator instructions, warnings and use and time limitations must also be read and understood by the wearer before use.
Before use of these respirators, a written respiratory protection program must be implemented, meeting all the requirements of OSHA 29 CFR 1910.134, including training and fit testing.