

Specification Sheet

Part Number: FSU16-E



Single-part insert creates smooth entry / exit point for wire and cables.

HelaGuard Metallic Conduit End Cap Insert, Flexible 0.38" (16mm) Dia, NPB Metal, 10/pkg

Article Number 166-90843

Type FSU16-E

Color Metal (ML)

Quantity Per pack

Product Description Nickel-plated brass end cap insert creates a smooth bore exit, protecting cables from damage. Twist-in ferrule serves as grounding core for spiral-constructed metallic conduit. Use with FSU, LFHU, FPU, SSU and FU-X series metallic conduit.

Short Description HelaGuard Metallic Conduit End Cap Insert, Flexible 0.38" (16mm) Dia, NPB Metal, 10/pkg

Global Part Name FSU16-E-NPB/PVC-ML

Length L (Imperial) 0.84

Length L (Metric) 21.3

Height H (Imperial) 0.79

Height H (Metric) 20.0

Nominal Diameter (Imperial) 0.38

Nominal Diameter (Metric) 16

Material Polyvinylchloride (PVC) Nickel Plated Brass (NPB)

Material Shortcut PVC NPB

UV Resistant (Yes/No) No

Operating Temperature -148°F to +572°F (-100°C to +300°C)

Reach Compliant (Article 33) No

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 7419805500

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)