
### S20KAC-P06MCC0-500S





#### General information

| Part number       | S20KAC-P06MCC0-500S |  |
|-------------------|---------------------|--|
| Termination       | solder              |  |
| Size              | 0                   |  |
| Locking principle | push                |  |
| Coding            | a_key               |  |
| Cable Diameter    | cable_mini_50       |  |
| Cable outlet      | bend_relief         |  |



# Contact insert description

| 6      |
|--------|
| pins   |
| 05mm   |
| peek   |
| 28_awg |
| solder |
| 04mm   |
|        |

reverse\_gender\_on\_request

# Technical information

| Max. creepage and air clearance distance | 07_mm    | 07_mm         |
|--|----------|---------------|
| Nominal current single contact           | 04_a     | iec_60512_5_2 |
| Nominal current insert                   | 3 A      | vde_0298_4    |
| Test voltage                             | 09_kv_ac | sae_13441     |

safety\_text

# Mechanical and environmental data

| Degree of protection* | ip68     |  |
|-----------------------|----------|--|
| Operating temperature | 40_120_c |  |
| Mating cycles         | 5000     |  |
| mated                 |          |  |

### Material and surface treatments

| Housing | m_chrome      |
|---------|---------------|
| Contact | cu_alloy_gold |

safety\_text\_2 ul\_text illustrative\_text