| _ | | | | | 2 | | | | | | | | 1 | | | |
|-------------|---|---|--|--------------|--|--|--|--|--|---------------------|-------------------------|-------------------------------|-----------------|------------------------|------|--|
| | THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE US | | | | | | | | | NY WAY I | DETRIMEN | NTAL TO THE | INTERESTS | OF PANDUIT CORP. | | |
| | | PANDUIT PART # | | STUD SIZE | DIMENSIONS in. [mm] | | | | | CA9 | CD-800(E | | - w | | | |
| | | | ENGLIS | H METRI | C L ± .03 [0,8] | $W\pm rac{.01}{[0,3]}$ | $C\pm \frac{.02}{[0,5]}$ | $M\pm\frac{.03}{[0,8]}$ | H± .01 [0,3] | SERIES CRIMP DIE | SERIES CRIMP DIE | | | STAMPI | NG | |
| | _ | PMV2-3FB-3 | К | M3 | .78 [19,8] | .23 [5,9] | .20 [5,1] | .64 [16,3] | .13 [3,3] | | | | | | | |
| | | PV14-6FB-3 | K #6 | M3,5 | .78 [19,8] | .28 [7,1] | .19 [4,8] | .64 [16,3] | .15 [3,8] | | | | | | | |
| | | PV14-6FNB-3 | K #6 | M3,5 | .78 [19,8] | .24 [6,2] | .19 [4,8] | .64 [16,3] | .15 [3,8] | | | | | H DIA | | |
| В | | PV14-8FB-3K PV14-10FB-3K PV14-10FNB-3K PMV2-5FB-3K | K #8 | M4 | .84 [21,3] .86 [21,8] .86 [21,8] .86 [21,8] | .31 [7,9] .34 [8,6] .31 [7,9] .34 [8,6] | .23 [5,9] .24 [6,2] .24 [6,2] .25 [6,4] | .68 [17,3] .70 [17,8] .70 [17,8] .70 [17,8] | .17 [4,3] .20 [5,0] .20 [5,0] .21 [5,3] | CD9_24 | CD-800-2 | _2 | | C RAD | | |
| | | | | | | | | | | 000 2/1 | | 2 | | | B | |
| | | | | | | | | | | | | | | HOUSING | G | |
| | | | | M5 | | | | | | | | | | | | |
| | | PV14-14FB-3 | K 1/4' | ' M6 | 1.03 [26.2] | .44 [11,2] | .32 [8,1] | .78 [19,8] | .27 [6,9] | | | | | | | |
| | | | | | | | PRES | S/APPLICATO | R COMPAT | IBILITY CH | ART | | FUNNEL | | | |
| | | | | | | | | _ | PRESS | CP-8 | - | 61 | | WIRE EN | | |
| | | NOTES: | | | | | | | APPLICATOR | CA9 CA-800 | | 800 | | CARR STRII | | |
| | 1. UL LISTED AND CSA CERTIFIED FOR: A. #16-14 AWG [1,5-2,5 mm ²] SOLID OR STRANDED COF | | | | | | | | | IRE | | | | | | |
| | B. 221°F [105°C] MAX. OPERATING TEMPERATURE C. 600 V. MAX. VOLTAGE RATING | | | | | | | | | | | | - | .17 [4,3] MAX. WIRE | | |
| N | 2. SEE www.panduit.com FOR PACKAGE QUANTITIES | | | | | | | | | | | | | | A. / | |
| | 3. MATERIAL: A. STAMPING: .03" [0,76] THK COPPER, TIN PLATED B. HOUSING: VINYL, BLUE (U)US | | | | | | | | | | | | | | | |
| | 4 | | | | ACKETS A | RE METRI | C FQUIV | AL ENT | | LIS | STED | CERTIFI | | | | |
| | | | | | | | | | | | 87H 2164 | LR3121 | 12 1 | | 1 | |
| | 5 | 5. WIRE 9 | STRIP | LENGT | H: 11/32 | -0 | [8,7mm | - <u></u>] | | | | | | | | |
| | | | | | FORK TERMINALS, 2 PC. VINYL INSULA | | | | | | | VINVI INCLILATED | | | | |
| A | | | | | | | | | | | #16–14, CONTINUOUS REEL | | | | | |
| | | | | | | | | | | | | WING | | | | |
| | | | | | | | | | | I TEM | REVISION NAME | N41080BA/07 | | | | |
| | | | | | | | | | | DATAS | ET FILE NAME | PANDUI | | | | |
| | 07 | 12/16 T | 12/16 TMR TMR RGB REVISED CERTIFICATION, METRIC TOL WAS TWO DECIMALS | | | | N41080-A | 41080 DI | UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] | | | | | | | |
| | 06 | 07/14 MBY JHNU RGB REVISED NOTES, MOVED TOOLS TO TABLE, REVISED | | | | N41080-A | 41080 | .X ± | .XXX | | SEE NOTES | | | | | |
| 0A/15 | 05 | 09.07.12 J | JBN LCA VMB ADDED METRIC EQUIVALENT. REVISED NOTES. UPDATED DRAWING TO CURRENT STANDARDS. | | | | A4108 | | | | | rawing number: A 4 1 0 8 0 | | | | |
| 010100DA/15 | REV | DATE E | зү снк | APR | | DESCRI | PTION | | ECN | | BY DATE | – RAKL | SCALE N.T.S. | SHT 1 0F 1 | SIZE | |
| | 2 | | | | | | | | | 1 | | | | | | |