

1.	Product: <u>89740</u> ⊠
	Electronic, 2 C #18 Str TC, FEP Ins, FEP Jkt, CMP
	11 Request Sample

# **Product Description**

High Temperature Electronic, 2 Conductor 18AWG (19x30) Tinned Copper, FEP Insulation, FEP Outer Jacket, CMP

### **Technical Specifications**

### **Product Overview**

Suitable Applicatior			emperature environn ice communications;	nents; chemical resistant; out panel wiring	door and burial	applications; low vo	ltage analog sig	nals (4-20ma, (	)-10v,); low '	voltage digital cor	ntrol (24v,
Construction I	Details										
Conductor											
Element No. of E	lements Size	Stranding	g Material								
Pair(s) 1	18 AWG	19x30	TC - Tinned Copp	per							
nsulation	Material		Nom. Thickness	Nom. Insulation Diameter	Color Code						
Pair(s) FEP - Flu	uorinated Ethylene	Propylene	0.007 in (0.18 mm)	0.057 in (1.4 mm)	Black & Red						
Outer Jacket											
Mate		Nom. Th		iameter							
FEP - Fluorinated E	Ethylene Propylene	0.015 in (0	0.38 mm) 0.144 in (	(3.66 mm)							
Overall Cable Diam (Nominal):	neter 0.144 i	n (3.66 mm)	l								

### **Electrical Characteristics**

(Nominal):

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Characteristic Impedence	Max. Current
Pair(s)	5.5 Ohm/1000ft	20 pF/ft (66 pF/m)	72 Ohm	5.4 Amps per Conductor at 25°C

## Voltage

UL Voltage Rating

300 V (CMP), 150 V (CL3P)

# **Mechanical Characteristics**

#### Temperature

UL Temperature	Operating
150°C	-70°C to +200°C

### Bend Radius

Stationary Min.Installation1.3 in (33 mm)1.3 in (33 m	
Max. Pull Tension:	49 lbs (22 kg)
Bulk Cable Weight:	15 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6, IEC 60332-1-2
NEC / UL Compliance:	Article 725, Article 800
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	9740

#### **Product Notes**

#### **History**

Update and Revision:

Revision Number: 0.506 Revision Date: 01-20-2023

## Part Numbers

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
89740 002100	Red	Reel	100 ft	612825221227	С
89740 002500	Red	Reel	500 ft	612825221258	С
89740 0021000	Red	Reel	1,000 ft	612825221234	С
89740 0023000	Red	Reel	3,000 ft	612825221241	СZ
89740 0025000	Red	Reel	5,000 ft	612825221265	СZ

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.