

156-00134



Article Number: 156-00134

Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .40" - .55", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00134

Type T50SVCOC10-14

Color Black (BK)

- Features and Benefits**
- Omega Clip can be turned 360 degrees allowing for orientation in any direction.
 - Design allows quick and easy installation by hand without the need for tools.
 - Multiple bundle diameters available for all different ranges of bundles.

Product Description Omega Clip Cable Ties provide the opportunity to attach a wire or hose to an existing bundle. Offering a full range of orientations, the wire/hose can be orientated in any direction in relations to the main harness. The Omega Clip design is ideally suited for easing the application process on the production floor by allowing for an easy one-step snap fit of the harness assembly to the wire or hose

Fixation Method (FF) Omega Clips

Identification Plate Position none

Tie Closure plastic pawl

Short Description Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .40" - .55", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 222 N

Length L (Imperial) 6.0 "

Length L (Metric) 155 mm

Attaches to Diameter (Imperial) 0.4 " - 0.55 "

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.08 "

Bundle Diameter Min. (Metric) 2.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Diameter Min. (Imperial) 0.4 "

Diameter Max. (Imperial) 0.55 "

Thickness T (Imperial) 0.05 "

Attaches to Diameter (Metric) 10.0 - 14.0

Thickness T (Metric) 1.35 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500
Carton Quantity 3000 Pieces
Weight (Metric) 2.69 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HIRHS
PA66HS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes