

EG-Series
EGS EG2 EN 230VAC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



In contrast to fuse terminals with signalled failure indication, an LED indicates a functioning fuse in this case.

General ordering data

Order No.	1115860000
Type	EGS EG2 EN 230VAC
Version	Active components, Fuse component
GTIN (EAN)	4008190123871
Qty.	10 pc(s).

EG-Series
EGS EG2 EN 230VAC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	20 mm	Net weight	41.8 g
-------	-------	------------	--------

Temperatures

Operating temperature	-25 °C...+55 °C	Storage temperature	-40 °C...+100 °C
-----------------------	-----------------	---------------------	------------------

General data

Height with TS 32	67.5 mm	Height with TS 35	63.5 mm
Optical function display	LED green	Protection degree	IP 20

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

technical data

Max. continuous voltage, U _c (AC)	230 V	Fuse, max.	6.3 A
--	-------	------------	-------

Connection data

Clamping range, rated connection	4 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	4 mm ²	Wire connection cross section, finely stranded, max.	4 mm ²

Classifications

ETIM 2.0	EC000943	ETIM 3.0	EC000943
UNSPSC	30-21-19-21	eClass 4.1	27-13-08-01
eClass 5.1	27-13-08-01	eClass 6.2	27-13-08-02
eClass 7.1	27-14-02-01		

Approvals

Approvals



ROHS Conform

Data sheet...

EG-Series
EGS EG2 EN 230VAC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

