



POS. NO	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
F 48 ROW N	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Q	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
U	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

AN ASTERISK „X” DENOTES A STANDARD CONTACT.  
AN ASTERISK „⊗” DENOTES A FMLB CONTACT.

- NOTES
- 1 MATERIAL:  
-HOUSING: THERMOPLASTIC POLYESTER, COLOR GREY.  
-CONTACTS: BRASS.
  - 2
  - 3 PLATING CONTACT: CONFIRMS TO IEC 60603-2 PERFORMANCE LEVEL II REQUIREMENT IN CONTACT AREA, Sn OVER Ni IN SOLDER POST
  - 4
  - 5
  - 6 SOLDER POSTS SUITABLE FOR P.C.B. HOLES  
0,8±0,05 OR 1,0±0,1 DIA.
  - 7 8 HOLES SUITABLE FOR KEYING PIN PN. 215916-1.
  - 8 KEYING HOLES TO BE DRILLED BY CUSTOMER.

SEE NOTE 1		SEE NOTE 3		SEE NOTE 1		1392406-4	
FINISH		MATERIAL		PARTNUMBER		CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED	
-		-		-		© COPYRIGHT 19 - BY Tyco Electronics EC N.V. ALL INTERNATIONAL RIGHTS RESERVED. Tyco PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION ,19	
B PER ECO-17-002455		SY SY		22FEB'17		Tyco Electronics EC N.V. Oostkamp - Belgium	
A SR10-0419-02		BC BC		20 Sep '02		NAME	
O -		BC BC		18 Sep '02		48 POS. DIN 41612 F MALE 90° SOLDER CONNECTOR	
LTR. REVISION RECORD		DR. CHK. DATE		DWG.No. C-1392406		REV.LTR. SHEET 1 OF 1 A3	
DR.: B. Colpoert		CHK.: B. Colpoert		APP.: B. Colpoert		REV. B	
DATE: -		DATE: -		DATE: -		10 of 1 A3	