ATGBICS SC-SC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m

Brand : ATGBICS

Product code: CAB-OM4-SC-SC-30M-D

Product name : SC-SC OM4, ATGBICS Fibre Optic Cable, Multimode, Duplex, Aqua, 30m

SC-SC OM4, ATGBICS Fibre Optic Cable, Multimode, Duplex, Aqua, 30m

ATGBICS SC-SC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m:

This product is high quality SC-SC (male to male) Fibre Patch Cable. The OM4 cable type has a higher attenuation that helps reduce losses over greater distances. It supports 10 Gigabit Ethernet at lengths measuring up to 550 meters, with 40 Gigabit and 100 Gigabit Ethernet measuring up to 150 meters. depending on the type of transceiver and wavelength. The OM4 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns.

ATGBICS SC-SC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m. Cable length: 30 m, Cable type: OFNR, Fibre optic type: OM4, Connector 1: SC, Connector 2: SC, Core diameter: 50 µm, Full duplex






1 pc(s)

FeaturesFeaturesCable length *30 mEthernetCable length *30 mEthernet interface type10 Gigabit Ethernet, 40 GigabitConnector 1 *SCInsertion loss0.2 dBConnector 2 *SCInsertion loss0.2 dBConnector 1 gender *MaleReturn loss50 dBConnector 2 gender *MaleCountry of originChinaConnector 2 gender *UPCCountry of originChinaConnector polish typeUPCCountry of originChinaCable type *OFNR Technical details RoHSFibre optic type *M4Sustainability certificatesRoHSProduct colour *Aqua colourOperating temperature (T-T)40 - 70 °CCalding diameter50 µmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeWeight & dimensions40 - 70 °CWavelengths supported850,1300 nmEdelaimeter2 nm				
Connector 1*SCEthernet interface typeEthernet, 100 Gigabit EthernetConnector 2*SCInsertion loss0.2 dBConnector 1 gender *MaleReturn loss50 dBConnector 2 gender *MaleJacket material *Polyvinyl chloride (PVC)Connector 2 gender *MaleCountry of originChinaConnector polish typeUPCCountry of originChinaCable type *OFNRTechnical detailsRoHSFibre optic type *OM4Sustainability certificatesRoHSProduct colour *Aqua colourDoesn't containHalogenFull duplexOperational conditionsCore diameter50 µmOperating temperature (T-T)-40 - 70 °CCladding diameter125 µmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensions	Features		Features	
Connector poinsi typeOPCTechnical detailsCable type *OFNRTechnical detailsFibre optic type *OM4Sustainability certificatesRoHSProduct colour *Aqua colourDoesn't containHalogenFull duplex✓Operational conditionsCore diameter50 µmCladding diameter125 µmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensions	Connector 1 *SCConnector 2 *SCConnector 1 gender *MaleConnector 2 gender *MaleConnector polish typeUPCCable type *OFNRFibre optic type *OM4	SC SC Male Male	Insertion loss Return loss Jacket material *	Ethernet, 100 Gigabit Ethernet 0.2 dB 50 dB Polyvinyl chloride (PVC)
Core diameter50 μmOperational conditionsCladding diameter125 μmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensions		OFNR OM4	Technical details Sustainability certificates	
Cladding diameter125 µmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensions	•	-	Operational conditions	
	Cladding diameter Fiber mode structure	125 μm Multi-mode	Storage temperature (T-T)	
			-	2 mm

Packaging data Quantity per pack



5056468736482

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.