

**Technical specification :**

Rated voltage: IEC 61076-2-104	60 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100


**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey
Shielding bush :	CuZn, nickel plated

**Installation specification:**

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

**Contact assignment:**



Part no:	Description:	Length L:	Cable:
42-10843	SAL - 8S - RK3 - 2 / G3	2m	PVC, UL 2464, grey, 3x0,25mm <sup>2</sup> Cable: 781-G32300
42-10844	SAL - 8S - RK3 - 3 / G3	3m	
42-10845	SAL - 8S - RK3 - 5 / G3	5m	
42-10846	SAL - 8S - RK3 - 10 / G3	10m	
42-xxxxx	SAL - 8S - RK3 - ... / G3	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 22.03.2011 VF Ä3945 Coupling nut modified, spanner flats added, data sheet modified	dim. in mm	<b>title:</b> Female connector M8x1 axial, 360°-shielding	
		date      name		
	tolerance of cable:    L <= 4m: L + 40mm L > 4m: L + 1%	drawn 26.10.09      Franz	<b>dwg no:</b>  42K1A176	
	general tolerance:    0      ± 0,50mm 0,0     ± 0,25mm 0,00   ± 0,10mm	appd. 27.10.09      Burschik		
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		<b>part no:</b> see table	