



Recommended PCB Layout  
(Top View)

**Material and Finish**

Insulator: High Temperature Thermoplastic with Glass-fiber Reinforcement, UL 94V-0 Rated, Color: Black

Shell: Steel, Nickel Plated

Contact Material:  
Plug - Brass

Contact Plating Options:  
Standard: Gold Flash on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

15 Option: 15u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

30 Option: 30u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

**Electrical Specifications**

Rated Current: 2A  
Rated Voltage: 30V RMS  
Insulation Resistance: 1000 Megohms Min. at 500V DC  
Contact Resistance: 13 milliohms Max.  
Dielectric Withstanding Voltage: 1000V for 1 Minute

**Mechanical Specifications**

Operating Temperature: -55°C to +105°C

Part Number	Contact Area Plating Finish
K22XHT-B25P-NJ	Gold Flash (Standard)
K22XHT-B25P-NJ15	15u" Gold (15 Option)
K22XHT-B25P-NJ30	30u" Gold (30 Option)



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	05/08/08	New Drawing	S. Vien	H. MA	S. Vien	04/11/08
A2	07/30/13	ECO #12-018	S. Vien	P. DalCanto		
A3	08/07/18	Address Update	G. Serrato	D. Shehan		

**K22XHT-B25P-NJ**

Right Angle D-Sub, Male, RoHS Compliant

Jackscrews Installed, 0.318" Footprint

