



4 Type

- N With plastic pad (only for IIG)
- E With rubber pad (only for IIG-EL)

Specification

- Threaded stud
Steel, zinc plated, blue passivated finish
- Base
Steel, nickel plated
- **IIG**
Plastic pad
Nylon
- **IIG-EL**
Rubber pad
Elastomer, non-skid
- **RoHS compliant**

On request

- Stainless steel version

Information

IIG and IIG-EL “Glide-Rite”™ industrial glides are an economical way of leveling light duty machines, cabinets, office furniture, or any type of light weight equipment. The steel with nickel plating provides a very decorative finish that is acceptable for all applications. The nylon pad is non-abrasive to the surface in which it is placed. The elastomer pad provides greater stability for non-skid applications, reduces noise, shock and vibration, and is oil resistant.

A coupling nut is not recommended to use for installation. Use a nut or tapped hole of 1 - 1 1/2 times the thread diameter of the threaded stud.

To insure a proper glide size, divide the machine weight by the number of mounts required. This will equal the pounds or load per mount.

see also...

- “Glide-Rite”™ Industrial Glides MIG / MIG-EL (Metric Size) → page 1496

<p>How to order (IIG)</p> <p>IIG-1.20-10X24-1.50-N</p>	<p>1 Base diameter d_1</p> <p>2 Thread d_2</p> <p>3 Stud length l_1</p> <p>4 Type N</p>
<p>How to order (IIG-EL)</p> <p>IIG-EL-1.20-10X24-1.50-E</p>	<p>1 Base diameter d_1</p> <p>2 Thread d_2</p> <p>3 Stud length l_1</p> <p>4 Type E</p>

Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ Thread	³ l ₁	l ₂	l ₃	l ₄	A/F	Max. load
1.20 30.5	10 x 24	1.50 38.1	0.75 19.1	0.374 9.5	0.138 3.5	0.156 4.0	250 lbf 1112.05 N
1.20 30.5	1/4 x 20	1.50 38.1	0.75 19.1	0.374 9.5	0.138 3.5	0.219 5.6	250 lbf 1112.05 N
1.20 30.5	5/16 x 18	1.50 38.1	0.75 19.1	0.374 9.5	0.138 3.5	0.250 6.4	250 lbf 1112.05 N
2.03 51.6	5/16 x 18	2.00 50.8	0.99 25.1	0.488 12.4	0.213 5.4	0.250 6.4	250 lbf 1112.05 N
2.03 51.6	3/8 x 16	2.00 50.8	0.99 25.1	0.488 12.4	0.213 5.4	0.313 8.0	250 lbf 1112.05 N
2.40 61.0	3/8 x 16	2.00 50.8	1.03 26.2	0.551 14.0	0.213 5.4	0.313 8.0	250 lbf 1112.05 N
2.40 61.0	3/8 x 16	4.00 101.6	1.03 26.2	0.551 14.0	0.213 5.4	0.313 8.0	250 lbf 1112.05 N
2.40 61.0	1/2 x 13	2.00 50.8	1.03 26.2	0.551 14.0	0.213 5.4	0.437 11.1	250 lbf 1112.05 N
2.40 61.0	1/2 x 13	4.00 101.6	1.03 26.2	0.551 14.0	0.213 5.4	0.437 11.1	250 lbf 1112.05 N
2.80 71.1	1/2 x 13	2.00 50.8	1.06 26.9	0.559 14.2	0.213 5.4	0.437 11.1	500 lbf 2224.11 N
2.80 71.1	1/2 x 13	4.00 101.6	1.06 26.9	0.559 14.2	0.213 5.4	0.437 11.1	500 lbf 2224.11 N
2.80 71.1	5/8 x 11	2.00 50.8	1.06 26.9	0.559 14.2	0.213 5.4	0.500 12.7	500 lbf 2224.11 N
2.80 71.1	5/8 x 11	4.00 101.6	1.06 26.9	0.559 14.2	0.213 5.4	0.500 12.7	500 lbf 2224.11 N
3.19 81.0	1/2 x 13	4.00 101.6	1.15 29.2	0.622 15.8	0.213 5.4	0.437 11.1	500 lbf 2224.11 N
3.19 81.0	1/2 x 13	6.00 152.4	1.15 29.2	0.622 15.8	0.213 5.4	0.437 11.1	500 lbf 2224.11 N
3.19 81.0	5/8 x 11	4.00 101.6	1.15 29.2	0.622 15.8	0.213 5.4	0.500 12.7	500 lbf 2224.11 N
3.19 81.0	5/8 x 11	6.00 152.4	1.15 29.2	0.622 15.8	0.213 5.4	0.500 12.7	500 lbf 2224.11 N

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10

