


International Rectifier

203DMQ... SERIES

SCHOTTKY RECTIFIER

200 Amp


**Major Ratings and Characteristics**

Characteristics	203DMQ...	Units
$I_{F(AV)}$ Rectangular waveform	200	A
V_{RRM} range	80 and 100	V
I_{FSM} @ $t_p = 5 \mu s$ sine	16,000	A
V_F @ $100A_{pk}$, $T_J = 125^\circ C$ (per leg)	0.70	V
T_J range	-55 to 175	°C

Description/ Features

The 203DMQ Schottky rectifier doubler module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to $175^\circ C$ junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- $175^\circ C T_J$ operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



203DMQ... Series

Bulletin PD-20579 rev. C 02/04

International
Rectifier

Voltage Ratings

Part number	203DMQ080	203DMQ100
V_R Max. DC Reverse Voltage (V)	80	100
V_{RWM}	Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	203DMQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5 (Per Leg)	200	A	50% duty cycle @ $T_C = 107^\circ\text{C}$, rectangular wave form
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	16,000	A	5μs Sine or 3μs Rect. pulse
	2,100		Following any rated load condition and with 10ms Sine or 6ms Rect. pulse rated V_{RRM} applied
E_{AS} Non-Repetitive Avalanche Energy (Per Leg)	15	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 1 \text{ Amps}$, $L = 30 \text{ mH}$
I_{AR} Repetitive Avalanche Current (Per Leg)	1	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	203DMQ	Units	Conditions
V_{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.86	V	@ 100A
	1.03	V	@ 200A
	0.70	V	@ 100A
	0.84	V	@ 200A
I_{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	3	mA	$T_J = 25^\circ\text{C}$
	40	mA	$T_J = 125^\circ\text{C}$
$V_{F(TO)}$ Threshold Voltage	0.50	V	$T_J = T_J$ max.
r_t Forward Slope Resistance	1.08	mΩ	
C_T Max. Junction Capacitance (Per Leg)	2,650	pF	$V_R = 5V_{DC}$, (test signal range 100KHz to 1MHz) 25°C
L_S Typical Series Inductance (Per Leg)	7.0	nH	From top of terminal hole to mounting plane
dv/dt Max. Voltage Rate of Change (Rated V_R)	10000	V/ μs	

Thermal-Mechanical Specifications

(1) Pulse Width < 300μs, Duty Cycle <2%

Parameters	203DMQ	Units	Conditions
T_J Max. Junction Temperature Range	-55 to 175	°C	
T_{stg} Max. Storage Temperature Range	-55 to 175	°C	
R_{thJC} Max. Thermal Resistance Junction to Case (Per Leg)	0.70	°C/W	DC operation * See Fig. 4
R_{thJC} Max. Thermal Resistance Junction to Case (Per Package)	0.35	°C/W	DC operation
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.10	°C/W	Mounting surface, smooth and greased
wt Approximate Weight	79 (2.80)	g (oz.)	
T Mounting Torque	Min. 24 (20)	Kg-cm (lbf-in)	
	Max. 35 (30)		
	Mounting Torque Center Hole Typ. 13.5 (12)		
	Terminal Torque Min. 35 (30)		
	Max. 46 (40)		
Case Style	TO-244AB Isolated		Modified JEDEC




Fig. 1 - Max. Forward Voltage Drop Characteristics
 (Per Leg)




Fig. 2 - Typical Values Of Reverse Current
 Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance
 Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)

203DMQ... Series

Bulletin PD-20579 rev. C 02/04

International
IR Rectifier




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

- (2) Formula used: $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$;
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{RI} \times I_R (1 - D)$; $I_R @ V_{RI} = 80\%$ rated V_R

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 02/04