



Part no.	Finish Pos.1	Finish Pos.2	Finish Pos.3	Finish Pos.4 + 5 + 7 + 6
132A22039X	GOLD FLASH over NICKEL	GOLD FLASH over NICKEL	NICKEL PLATED	GOLD FLASH over NICKEL
132J22039X	min. 50µin HARD GOLD over min. 50µin NICKEL	min. 30 min HARD GOLD over min. 50 min NICKEL	NICKEL PLATED	GOLD FLASH over NICKEL

ASSEMBLY TOOLING:
 1. CENTER CONTACT:
 SOLDERED
 2. OUTER CONDUCTOR:
 SOLDERED OR CRIMPED
 USE CRIMP TOOL: 360X10519X
 WITH TOOL INSERT: 360X11039X
 INSERT CAVITY B: HEX 3.83 / .151"

Directive 2011/65/EU RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		DO NOT ALTER CAD DRAWING BY HAND		tolerance		scale: 8:1	
				dim. in mm		material:	
				date	name	title: COAXIAL CONTACT SOCKET 90°, 50 OHM for Cable RG 316U double braided inner conductor for solder termination outer conductor for crimp- or solder termination	
				drawn 18.08.2014	Heinrich		
				appd. 18.08.2014	Koch		
				norm			
				d-old		dwg no:	
				a	Original	13K1A4748	
				rev.	description	date	DIN-A3
							sh: 1
							part no: