

## SINGLE SUPPLY HI-SLEW RATE DUAL OPERATIONAL AMPLIFIER

### ■ GENERAL DESCRIPTION


The NJM2717 is a high slew rate single supply dual operational amplifier. It offers excellent features of a 40V/us (typ.) high slew rate in a single supply and low operating voltage from 2.7V, which provide a benefit to buffer, filter and ground level signal detection circuit design. Therefore The NJM2717 is suitable for CCD buffer and AD/DA converter buffer using in facsimile/scanner, current detector in inverter controller, PWM motor controller and Tuner/Communication devices.

The NJM2717 is available in a wide variety packages 8-lead DIP, and 8-lead surface-mount packages of SOP (DMP), SSOP and MSOP (TVSP).


### ■ PACKAGE OUTLINE



NJM2717D  
(DIP8)



NJM2717M  
(DMP8)



NJM2717V  
(SSOP8)




NJM2717RB1  
(MSOP8 (TVSP8))

### ■ FEATURES

- Single Supply
- Operating Voltage 2.7V to 12V
- High Slew Rate 40V/ $\mu$ s Typ. (at  $V^+=5V$ )
- Operating Current 8mA typ. (at  $V^+=5V$ )
- Output Voltage Range  $V_{OH} \geq 4.5V$  Typ. (at  $V^+=5V$ ,  $R_L=4k\Omega$ )  
 $V_{OL} \leq 0.05V$  Typ. (at  $V^+=5V$ ,  $R_L=4k\Omega$ )
- Bipolar Technology
- Package Outline DIP8,  
DMP8,  
SSOP8,  
MSOP8 (TVSP8) MEET JEDEC MO-187-DA / THIN TYPE

### ■ PIN CONFIGURATION



#### PIN FUNCTION

1. A OUTPUT
2. A -INPUT
3. A +INPUT
4. GND
5. B +INPUT
6. B -INPUT
7. B OUTPUT
8.  $V^+$

NJM2717D

NJM2717M

NJM2717V

NJM2717RB1

(Top View)

# NJM2717

## ■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V <sup>+</sup>	15.0	V
Differential Input Voltage	V <sub>ID</sub>	± 3	V
Input Common Mode Voltage Range	V <sub>ICM</sub>	-0.3 to +15.0(Note 1)	V
Power Dissipation	P <sub>D</sub>	(DIP8) 500 (DMP8) 300 (SSOP8) 250 (MSOP8 (TVSP8)) 320	mW
Output Sink Current	I <sub>SINK</sub>	10	mA
Operating Temperature Range	T <sub>opr</sub>	-40 to +85	°C
Storage Temperature Range	T <sub>stg</sub>	-40 to +125	°C

(Note 1) For supply voltage less than 15V, the absolute maximum input voltage is equal to the supply voltage.

## ■ RECOMMENDED OPERATING CONDITION

(Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	V <sup>+</sup>	2.7 to 12.0	V

## ■ ELECTRICAL CHARACTERISTICS

### •DC CHARACTERISTICS

(V<sup>+</sup>=5V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	I <sub>CC</sub>	R <sub>L</sub> =∞, no signal	-	8.0	11.0	mA
Input Offset Voltage	V <sub>IO</sub>	R <sub>S</sub> =0Ω	-	1	11	mV
Input Bias Current	I <sub>B</sub>		-	2	4.4	μA
Input Offset Current	I <sub>IO</sub>		-	0.2	0.5	μA
Voltage Gain	A <sub>V</sub>	R <sub>L</sub> ≥ 10kΩ, V <sub>O</sub> =1.5V to 3.5V	60	75	-	dB
Common Mode Rejection Ratio	CMR	0V ≤ V <sub>CM</sub> ≤ 3.8V	45	80	-	dB
Supply Voltage Rejection Ratio	SVR	V <sup>+</sup> =4V to 8V	50	85	-	dB
Output Voltage 1	V <sub>OH1</sub>	R <sub>L</sub> =4kΩ to GND	4.3	4.5	-	V
	V <sub>OL1</sub>		-	0.05	0.1	V
Output Voltage 2	V <sub>OH2</sub>	R <sub>L</sub> =4kΩ to 2.5V	4.5	4.7	-	V
	V <sub>OL2</sub>		-	0.1	0.5	V
Output Source Current	I <sub>SOURCE</sub>		1	2.5	-	mA
Output Sink Current	I <sub>SINK</sub>		2.5	6	-	mA
Input Common Mode Voltage Range	V <sub>ICM</sub>	0 to 3.8	-	-	-	V

### •AC CHARACTERISTICS

(V<sup>+</sup>=5V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Unity Gain Bandwidth	f <sub>T</sub>		-	20	-	MHz

### •TRANSIENT CHARACTERISTICS

(V<sup>+</sup>=5V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR		-	40	-	V/μs

## ■ ELECTRICAL CHARACTERISTICS

## ● DC CHARACTERISTICS

(V<sup>+</sup>=12V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	I <sub>CC</sub>	R <sub>L</sub> =∞, no signal	-	10.0	14.5	mA
Input Offset Voltage	V <sub>IO</sub>	R <sub>S</sub> =0Ω	-	1	12	mV
Input Bias Current	I <sub>B</sub>		-	2.1	4.4	μA
Input Offset Current	I <sub>IO</sub>		-	0.2	1	μA
Voltage Gain	A <sub>V</sub>	R <sub>L</sub> ≥ 10kΩ, V <sub>O</sub> =2V to 10V	60	80	-	dB
Common Mode Rejection Ratio	CMR	0V ≤ V <sub>CM</sub> ≤ 10.8V	45	80	-	dB
Supply Voltage Rejection Ratio	SVR	V <sup>+</sup> =8V to 12V	50	85	-	dB
Output Voltage 1	V <sub>OH1</sub>	R <sub>L</sub> =10kΩ to GND	11.3	11.5	-	V
	V <sub>OL1</sub>		-	0.1	0.3	V
Output Voltage 2	V <sub>OH2</sub>	R <sub>L</sub> =10kΩ to 6V	11.5	11.7	-	V
	V <sub>OL2</sub>		-	0.1	0.5	V
Output Source Current	I <sub>SOURCE</sub>		1	3	-	mA
Output Sink Current	I <sub>SINK</sub>		2.5	8	-	mA
Input Common Mode Voltage Range	V <sub>ICM</sub>		0 to 10.8	-	-	V

## ● AC CHARACTERISTICS

(V<sup>+</sup>=12V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Unity Gain Bandwidth	f <sub>T</sub>		-	21	-	MHz

## ● TRANSIENT CHARACTERISTICS

(V<sup>+</sup>=12V,Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR		-	45	-	V/μs

# NJM2717

## ■ ELECTRICAL CHARACTERISTICS

### • DC CHARACTERISTICS

( $V^+=2.7V$ ,  $T_a=25^\circ C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	$I_{CC}$	$R_L=\infty$ , no signal	-	6	8.5	mA
Input Offset Voltage	$V_{IO}$	$R_S=0\Omega$	-	1	10	mV
Input Bias Current	$I_B$		-	1.7	4.4	$\mu A$
Input Offset Current	$I_{IO}$		-	0.2	0.5	$\mu A$
Voltage Gain	$A_V$	$R_L \geq 10k\Omega$ , $V_O=0.85V$ to $1.85V$	60	73	-	dB
Common Mode Rejection Ratio	CMR	$0V \leq V_{CM} \leq 1.5V$	45	80	-	dB
Supply Voltage Rejection Ratio	SVR	$V^+=2.7V$ to $4V$	50	75	-	dB
Output Voltage 1	$V_{OH1}$	$R_L=4k\Omega$ to GND	2.5	2.6	-	V
	$V_{OL1}$		-	0.05	0.1	V
Output Voltage 2	$V_{OH2}$	$R_L=4k\Omega$ to $1.35V$	2.6	2.65	-	V
	$V_{OL2}$		-	0.1	0.2	V
Output Source Current	$I_{SOURCE}$		1	2.5	-	mA
Output Sink Current	$I_{SINK}$		2.5	5	-	mA
Input Common Mode Voltage Range	$V_{ICM}$		0 to 1.5	-	-	V

### • AC CHARACTERISTICS

( $V^+=2.7V$ ,  $T_a=25^\circ C$ )





PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Unity Gain Bandwidth	$f_T$		-	19	-	MHz

### • TRANSIENT CHARACTERISTICS

( $V^+=2.7V$ ,  $T_a=25^\circ C$ )







PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR		-	30	-	V/ $\mu s$

## ■ Typical Characteristics




# NJM2717

## ■ Typical Characteristics




## ■ Typical Characteristics


**Maximum Output Voltage vs. Supply Voltage**  
 $G_V=OPEN, R_L=4k\Omega$




**Maximum Output Voltage vs. Ambient Temperature**  
 $G_V=OPEN, RL=4k\Omega$




**Maximum Output Voltage vs. Load Resistance**  
 $G_V=OPEN, T_a=+25^\circ C$




**Maximum Output Voltage vs. Load Resistance**  
 $V^+/V^- = \pm 1.35V, G_V=OPEN$



**Maximum Output Voltage vs. Load Resistance**  
 $V^+/V^- = \pm 2.5V, G_V=OPEN$




**Maximum Output voltage vs. Load Resistance**  
 $V^+/V^- = \pm 6.0V, G_V=OPEN$




# NJM2717

## ■ Typical Characteristics


**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+2.7V, V=$ GND,  $G_V=$ OPEN




**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+2.7V, V=$ GND,  $G_V=$ OPEN




**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+5.0V, V=$ GND,  $G_V=$ OPEN




**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+5.0V, V=$ GND,  $G_V=$ OPEN









**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+12.0V, V=$ GND,  $G_V=$ OPEN



**Maximum Output Voltage  
vs. Load Resistance**  
 $V^+=+12.0V, V=$ GND,  $G_V=$ OPEN








## ■ Typical Characteristics



# NJM2717

## ■ Typical Characteristics



**[CAUTION]**  
The specifications on this data book are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this data book are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.