



Unsurpassed in Cable Protection and Strain Relief

Technical Data Shee



CERTIFICATIONS



ROHRFLEX PA 6-UL-SD



Aerosusa.com
service@aerosusa.com
855.393.9905

Corrugated all-plastic tubing, internally and externally corrugated. UL listed 1660. LFNC-C. For installation in accordance with Article 356 of ANSI / NFPA 70, National Electric Code, NEC. Ideal for static, high impact applications.

Material: Plastics PA 6

Temperature:
-13°F ... +248°F
-25°C ... +120°C

Flammability: V2 [UL 94]

Protection Class: IP 68

Color: Black

Properties:

- air- and liquid-tight
- oil resistant up to 80°C
- benzine resistant
- widely resistant to acid and solvents
- free of silicone, cadmium and halogen
- highly self-extinguishing
- flame retardant
- UV-resistant
- UL 1660 | CSA C22.2 Nr. 227.2.1-14
- REACH and RoHS compliant

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Technical Data Sheet

Aerosusa.com
service@aerosusa.com
855.393.9905

Product #	Profile	Color	Trade Size	AD	ID x OD (in)	Dyn BR (in)	Stat BR (in)	lb/ft	PU
0238.202.016	Fine	Black	1/2"	21.2	0.63 x 0.83	2.95	1.97	0.0504	164 FT
0238.202.023	Fine	Black	3/4"	28.5	0.89 x 1.12	3.94	2.36	0.0806	164 FT
0238.202.029	Fine	Black	1"	34.5	1.12 x 1.36	4.72	2.76	0.1042	82 FT
0238.202.036	Fine	Black	1 1/4"	42.5	1.40 x 1.67	5.91	3.94	0.1492	82 FT
0238.202.048	Fine	Black	1 1/2"	54.5	1.87 x 2.15	7.48	4.33	0.2016	82 FT

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103