

**Ratings**

Voltage: 300 V  
Temperature: -80~200 °C  
Flammability: VW-1  
Oil resistance: 60 °C  
≥50% elongation and tensile strength after aging

**Conductor**

Conductor count: 1  
Gauge: 16 AWG 1.34 mm<sup>2</sup>  
Material: tinned copper strands  
Strand size: Ø0.3 mm x 19  
Resistance at 20 °C: 14.6 Ω /km max


**Insulator**

Material: Fluorinated ethylene propylene (FEP)  
Color: gray  
Diameter: Ø2.16 ±0.10 mm  
Nominal thickness: 0.33 mm  
Resistance at 20 °C: 2.5 MΩ /kft min

**Wire marking:** E339579 UL AWM STYLE 1332 16AWG 200°C 300V  
VW-1 --- cUL AWM I A/B 200°C 300V FT1 TENSILITY

**Mechanical Tests**

After aging at 232±1°C for 7 days  
Minimum tensile strength 1.76 kgf/mm<sup>2</sup>  
Minimum elongation 200% original



|           |           |                 |
|-----------|-----------|-----------------|
| Revision: | Date:     | Description:    |
| A         | 5/23/2022 | Initial release |
|           |           |                 |
|           |           |                 |
|           |           |                 |

Prepared: **MP**  
Digitally signed by MP  
Date: 2022.05.24  
15:49:50 -07'00'

Verified: **PB**  
Digitally signed by PB  
Date: 2022.05.27  
14:04:50 -07'00'

Dimensions are in millimeters.  
Tolerances:  
X: ± 0.5 mm  
X.X: ± 0.3 mm  
X.XX: ± 0.05 mm

Notes:  
RoHS compliant

Function test: no open, no short circuit, no Intermittent

Description:  
Wire, hook-up, TS, 16 AWG, UL 1332, 300V, 200C, 2.16 mm, FEP, gray

**TENSILITY**

tel 1.541.323.3228 800 877.670.7118  
fax 1.541.323.4202 web tensility.com

|             |              |
|-------------|--------------|
| Size:       | Part number: |
| A           | 30-02539     |
| Scale: 18:1 | Sheet 1 of 1 |