




FineAdjust Applicator Specification Sheet Order No. 63901-5200



FEATURES

- Quick punch removal with the push of a button for fast and easy tooling change
- Applicator designed to industry standard mounting and shut height 135.80mm (5.346")
- Quick set-up time; plus the crimp height, track and feed adjustments can be set without removing the applicator from the press
- Fine adjustment allows users to achieve target with little effort by adjusting in increments of .015mm (.0006") for conductor crimp height and .063mm (.0025") for insulation height
- Independent adjustment rings allow users to quickly adjust the conductor or insulation crimp height without affecting each other
- Directly adapts to most automatic wire processing machines


SCOPE

Products: 2.00mm (.079") Pitch Female Crimp Terminal, 22-28 AWG.

| Terminal Series No. | Terminal Order No. | Wire Size | | Insulation Diameter | | | | Strip Length | |
|---------------------|--------------------|-----------|-----------------|---------------------|-------|--------------|-----------|--------------|-----------|
| | | | | IPC/WHMA-A60 (1) | | Terminal (2) | | | |
| | | AWG | mm ² | mm | In. | mm | In. | mm | In. |
| 56134 | 56134-8000 | 22 | 0.34 | 1.65 | 0.065 | 1.25-1.70 | .049-.067 | 1.60-2.00 | .063-.079 |
| | | 24 | 0.20 | 1.45 | 0.057 | | | | |
| | | 26 | 0.13 | 1.30 | 0.051 | | | | |
| | 56134-9000 | 22 | 0.34 | 1.65 | 0.065 | 0.90-1.70 | .035-.067 | 1.60-2.00 | .063-.079 |
| | | 24 | 0.20 | 1.45 | 0.057 | | | | |
| | | 26 | 0.13 | 1.30 | 0.051 | | | | |
| | | 28 (3) | - | - | - | - | - | - | |

(1) To achieve optimum IPC-A620 Class 2 insulation crimps, use this insulation OD using UL1007 wire.
 (2) Overall insulation OD specification for terminal.
 (3) 28 AWG wire is not recommended for use in this terminal, use 22-26 AWG wire for better crimp quality.

DEFINITION OF TERMS



The above terminal drawing is a generic terminal representation. It is not an image of any terminal listed in the scope.

CRIMP SPECIFICATION

| Terminal Series No. | Bell mouth | | Cut-off Tab Maximum | | Conductor Brush | |
|---------------------|------------|-----------|---------------------|------|-----------------|-----------|
| | mm | In. | mm | In. | mm | In. |
| 56134 | 0.05-0.40 | .002-.016 | 0.30 | .012 | 0.10-0.70 | .004-.028 |

| Terminal Series No. | Bend up | Bend down | Twist | Roll | Punch Width (Ref) | | | | Seam Seam shall not be open and no wire allowed out of the crimping area |
|---------------------|---------|-----------|--------|------|-------------------|------|------------|------|---|
| | Degree | | Degree | | Conductor | | Insulation | | |
| | mm | In | mm | In | mm | In | mm | In | |
| 56134 | 3 ° | 3 ° | 3 ° | 6 ° | 1.20 | .047 | 1.50 | .059 | |

After crimping, the crimp profiles should measure the following:

| Terminal Order No. | Wire Size | | Conductor | | | | Insulation | | | | Pull Force Minimum | |
|--------------------|-----------|-----------------|--------------|-----------|-------------------|-----------|--------------|-----------|-------------------|-----------|--------------------|-----|
| | | | Crimp Height | | Crimp Width (Ref) | | Crimp Height | | Crimp Width (Ref) | | | |
| | AWG | mm ² | mm | In. | mm | In. | mm | In. | mm | In. | N | Lb. |
| 56134-8000 | 22 | 0.34 | 0.70-0.75 | .028-.030 | 1.18-1.28 | .046-.050 | 1.85-1.95 | .073-.077 | 1.55-1.75 | .061-.069 | 44.1 | 9.9 |
| | 24 | 0.20 | 0.67-0.72 | .026-.028 | 1.18-1.28 | .046-.050 | 1.80-1.90 | .071-.075 | 1.55-1.75 | .061-.069 | 29.4 | 6.6 |
| | 26 | 0.13 | 0.61-0.66 | .024-.026 | 1.18-1.28 | .046-.050 | 1.75-1.85 | .069-.073 | 1.55-1.75 | .061-.069 | 19.6 | 4.4 |
| 56134-9000 | 22 | 0.34 | 0.70-0.75 | .028-.030 | 1.18-1.28 | .046-.050 | 1.85-1.95 | .073-.077 | 1.55-1.75 | .061-.069 | 44.1 | 9.9 |
| | 24 | 0.20 | 0.67-0.72 | .026-.028 | 1.18-1.28 | .046-.050 | 1.80-1.90 | .071-.075 | 1.55-1.75 | .061-.069 | 29.4 | 6.6 |
| | 26 | 0.13 | 0.61-0.66 | .024-.026 | 1.18-1.28 | .046-.050 | 1.75-1.85 | .069-.073 | 1.55-1.75 | .061-.069 | 19.6 | 4.4 |

T Tool Qualification Notes:

1. This Applicator was qualified to the above specifications with UL1007 wire.
*An insulation diameter larger than .051" may cause the insulation grips to pierce the insulation on both sides of the insulation crimp. The customer should determine the suitability for their application.
2. Pull Force should be measured with no influence from the insulation crimp.
3. The above specifications are guidelines to an optimum crimp.

PARTS LIST

| FineAdjust Applicator 63901-5200 | | | | |
|--|------------|-----------------|------------------------------------|----------|
| Item | Order No | Engineering No. | Description | Quantity |
| Perishable Tooling | | | | |
| | 63901-5270 | 63901-5270 | Tool Kit (All "Y" Items) | REF |
| 1 | 63444-1207 | 63444-1207 | Conductor Punch | 1 Y |
| 2 | 63445-1213 | 63445-1213 | Conductor Anvil | 1 Y |
| 3 | 63446-1510 | 63446-1510 | Insulation Punch | 1 Y |
| 4 | 63445-1504 | 63445-1504 | Insulation Anvil | 1 Y |
| 5 | 63443-0002 | 63443-0002 | Cut-Off Plunger Front | 1 Y |
| 6 | 63443-0012 | 63443-0012 | Plunger Retainer Front | 1 Y |
| Other Components | | | | |
| 7 | 11-18-4083 | 60707-8 | Front Cover | 1 |
| 8 | 11-24-1067 | 4996-4 | Cut-off Plunger Spring | 1 |
| 9 | 63443-0009 | 63443-0009 | Scrap Chute Front | 1 |
| 10 | 63443-0024 | 63443-0024 | Lower Tooling Key | 1 |
| 11 | 63443-0090 | 63443-0090 | Wire Stop | 1 |
| 12 | 63443-1703 | 63443-1703 | 17.30mm Height Spacer | 1 |
| 13 | 63443-2210 | 63443-2210 | 10.0mm Coarse Spacer | 2 |
| 14 | 63443-3160 | 63443-3160 | Plunger Striker Front | 1 |
| 15 | 63443-6111 | 63443-6111 | Rear Cover | 1 |
| Frame | | | | |
| 16 | 63800-4901 | 63800-4901 | Top | 1 |
| 17 | 63801-3281 | 63801-3281 | Base | 1 |
| 18 | 63801-4650 | 63801-4650 | Track | 1 |
| Hardware | | | | |
| 19 | N/A | N/A | M3 by 6 Long FHCS | 1** |
| 20 | N/A | N/A | M3 by 6 Long SHCS | 2** |
| 21 | N/A | N/A | M4 by 6 Long SHCS | 2** |
| 22 | N/A | N/A | M4 by 12 Long BHCS | 2** |
| 23 | N/A | N/A | M4 by 45 Long SHCS | 2** |
| 24 | N/A | N/A | M5 by 12 Long SHCS | 1** |
| 25 | N/A | N/A | #10-32 by 3/8" Long Flat Point SSS | 1** |
| 26 | N/A | N/A | #10-32 Hex Jam Nut | 1** |
| ** Available from an industrial supply company such as MSC (1-800-645-7270). | | | | |

Assembly Drawing




Figure 1

NOTES

1. Molex recommends an extra perishable tooling kit be maintained at your facility.
2. Verify tooling alignment by manually cycling the press and Applicator before crimping under power. Check that all screws are tight.
3. Slugs, Terminals, Dirt and Oil should be kept clear of work area.
4. Wear safety glasses at all times.
5. For recommended maintenance refer to the FineAdjust Manual.

CAUTION: This applicator should only be used in a press with a shut height of 135.80 mm (5.346"). Tooling damage could result at a lower setting.

CAUTION: To prevent injury never operate this Applicator without the guards supplied with the press or wire-processing machine in place. Reference the press or wire processing manufacturer's instruction manual.

CAUTION: Molex crimp specifications are valid only when used with Molex terminals, applicators and tooling.

Americas Headquarters
Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Far East North Headquarters
Yamato, Kanagawa, Japan
81-462-65-2324
feninfo@molex.com

Far East South Headquarters
Jurong, Singapore
65-6-268-6868
fesinfo@molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
630-969-4550
Fax: 630-969-1352

Visit our Web site at <http://www.molex.com>