292180-1 ~ ACTIVE

CT Hybrid Drawer

TE Internal #: 292180-1 Connector Assembly, Plug to Plug Relay Header, Wire-to-Wire, 6 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, CT Hybrid Drawer

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Connector Assembly

Connector & Housing Type: Plug to Plug Relay Header

Connector System: Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 2 mm [.079 in]

Features

Product Type Features

Connector Product Type

Connector & Housing Type

Connector Assembly

Plug to Plug Relay Header

Connector System	Wire-to-Wire			
Sealable	No			
Connector & Contact Terminates To	Wire & Cable			
Configuration Features				
Number of Power Positions	2			
Number of Signal Positions	4			
Number of Positions	6			
Number of Rows	2			
Electrical Characteristics				
Electrical Characteristics				
Electrical Characteristics Dielectric Withstanding Voltage (Max)	1800 VAC			
	1800 VAC 100 MΩ			
Dielectric Withstanding Voltage (Max)				
Dielectric Withstanding Voltage (Max) Insulation Resistance	100 MΩ			
Dielectric Withstanding Voltage (Max) Insulation Resistance Operating Voltage	100 MΩ			

Connector Assembly, Plug to Plug Relay Header, Wire-to-Wire, 6 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, CT Hybrid Drawer



Contact Features

Contact Type	Pin			
Contact Base Material	Copper Alloy			
Contact Current Rating (Max)	15 A			
Termination Features				
Termination Method to Wire & Cable	Crimp			
Mechanical Attachment				
Strain Relief	Without			
Panel Mount Feature	With			
PCB Mount Retention	Without			
Panel Mount Feature Type	Mounting Ears			
Mating Retention	Without			
Connector Mounting Type	Panel Mount			
Housing Features				
Housing Material	Thermoplastic			
Centerline (Pitch)	2 mm[.079 in]			

Dimensions

Connector Length	33 mm[1.299 in]		
Connector Height	16.4 mm[.646 in]		
Connector Width	18 mm[.709 in]		
Compatible Insulation Diameter Range	1.4 – 2.4 mm[.055 – .094 in]		
Wire Size	.2 – 1.25 mm²		
Usage Conditions			
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]		
Operation/Application			
Circuit Application	Power & Signal		
Industry Standards			
Glow Wire Rating	Standard Part - Not Glow Wire		
UL Flammability Rating	UL 94V-0		
Packaging Features			
Packaging Quantity	400		
Packaging Method	Tray		

C For support call+1 800 522 6752

Connector Assembly, Plug to Plug Relay Header, Wire-to-Wire, 6 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, CT Hybrid Drawer



Other

Discrete Wire Connector Comment	Mating Connector - 292184-1					
Product Compliance For compliance documentation, visit the product page on TE.com>						
EU RoHS Directive 2011/65/EU	Compliant					
EU ELV Directive 2000/53/EC	Compliant					
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold					
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC					
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.					
Solder Process Capability	Not applicable for solder process capability					

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



Also in the Series | CT Hybrid Drawer

Connector Assembly, Plug to Plug Relay Header, Wire-to-Wire, 6 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, CT Hybrid Drawer





Customers Also Bought



TE Part #62759-1 SPLICE 400-1300 .016 BR	TE Part #175149-2 AMP UNIVE. POWER CONN TAB CONT	TE Part #62814-1 250 FASTON FLAG REC 22-18 AWG BR	TE Part #764619-0 CWT-7-W122-5
d d			
TE TE	STE		
TE Part #962834-1 FF 374 REC 2.5-4 MM2 PLAIN CUSN4	TE Part #42640-1 250 FASTON REC 22-18 AWG BR		

Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_292180-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_292180-1_A.3d_igs.zip

Connector Assembly, Plug to Plug Relay Header, Wire-to-Wire, 6 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, CT Hybrid Drawer



English

Customer View Model ENG_CVM_292180-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages POWER_CONNECTORS_CATALOG_SEC02_CABLE_MOUNTED

English

Low Power Drawer Connectors QRG

English

Product Specifications

Application Specification

English

Crimping Hybrid Mini Drawer Connector Power Line Contact

English

Product Environmental Compliance MD_292180-1_012020152118_dmtec

English

MD_292180-1_012020152118_dmtec

English

Agency Approvals

UL Report

English