		4		<u> </u>	3			2			1	
_	ITEM	CONNECTOR PART NO.		DESCRIPTION				qqA	licable	Housings		
1		SSHL-003T-P0.2		DR CONTACT								
2		UL1571 (BCD), 28 AWG	BLACK _1					SHL		\sum_{2}		
							NO. OF CIRCUITS			NO. OF CIRCUITS	HOUSING PART NO)
							2	SHLP-02V-S	Б-В	2	NSHR-02V-S	
							5	SHLP-05V-S	5-В	3	NSHR-03V-S	
							6	SHLP-06V-S	Б-В	4	NSHR-04V-S	
							7	SHLP-07V-S	Б-В	5	NSHR-05V-S	
							8	SHLP-08V-S	Б-В	6	NSHR-06V-S	
							10	SHLP-10V-S	5-В	7	NSHR-07V-S	
							11	SHLP-11V-S	5-В	8	NSHR-08V-S	
							12	SHLP-12V-S	5-В	9	NSHR-09V-S	
							14	SHLP-14V-S	5-В	10	NSHR-10V-S	
							16	SHLP-16V-S	5-В	11	NSHR-11V-S	
							20	SHLP-20V-S	5-В	12	NSHR-12V-S	
							22	SHLP-22V-S	5-В	13	NSHR-13V-S	
							26	SHLP-26V-S	5-В	14	NSHR-14V-S	
							30	SHLP-30V-S	D	15	NSHR-15V-S	
									5-0	15	11214-126-2	
	1				310.6 +/- 5.0) 304.8 +/- 5.0)	15		
			2				SCALE 1:1)	JST	Electrical Specifications	
3	<u> </u>	Add electrical specifica				SP	SCALE 1: 1 DIMENSIONS All dimensions are tolerance of +/	e in MM with a /- 3.0 unless	DESCRIPTION	JST	Electrical Specifications Current: 1.0A AC/DC Voltage: 50V AC/DC	
3	~ -	Add electrical specifica Added the NSH series a	ations		304.8 +/- 5.0		SCALE 1: 1 DIMENSIONS All dimensions are	e in MM with a /- 3.0 unless specified.	DESCRIPTION	SHL & NSH Series Stand DOUBLE-END	Electrical Specifications Current: 1.0A AC/DC Voltage: 50V AC/DC	
-			ations applicable housing	ng part numbers	304.8 +/- 5.0 7/2/2018	7 SP	SCALE 1: 1 DIMENSIONS All dimensions are tolerance of +/ otherwise s	e in MM with a /- 3.0 unless specified.	DESCRIPTION 1.0 mm Pitch	DOUBLE-END	Electrical Specifications Current: 1.0A AC/DC Voltage: 50V AC/DC dard Leads- 12" Inside Lengt LEADS	