


AE-B64-SP1

DIP40/BGA64 specialized adapter for FLASH memory.
 Device package dimensions: 13.0 x 11.0 x 1.4 mm, 1.0 mm pitch.



Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

Adapter Connection Table:

DIP-40	BGA-64	U1, 74HC573	U2, 74HC573	C1, 150pF	C2, 0.1uF
1	D8,F1				
2	G1				
3		11	11	1	
4	B5				
5	F8				
6	G8				
7	A5				
8	A4				
9	B4				
10	A3				
11	C3				
12	D3				
13	B2				
14	A2				
15	C2				
16	D2				
17	E2				
18	B1				
19					

AE-B64-SP1

20	H2,H7,E8	1, 10	1, 10	2	2
21	F2				
22	G2				
23	E3	2			
24	F3		2		
25	H3	3			
26	G3		3		
27	E4	4			
28	F4		4		
29	H4	5			
30	G4		5		
31	H5	6			
32	F5		6		
33	E5	7			
34	G6		7		
35	H6	8			
36	F6		8		
37	E6	9			
38	G7		9		
39	F7				
40	G5	20	20		1
	C8		12		
	B8		13		
	D7	12			
	C7	13			
	A7	14			
	B7	15			
	D6	16			
	C6	17			
	A6	18			
	B6	19			
	D5		16		
	D4		15		
	C5		14		
	C4		17		
	B3		18		
	E7		19		