# FIS 1RU HIGH DENSITY RACK MOUNT ENCLOSURE





## **FEATURES**

- Slide Out Tray with Spring Loaded Stop Latch
- Holds (3) LGX Adapter Plates, Cassettes, or Modules
- Multiple Tie Downs and Cable Retention Brackets
- Hinged Front and Rear Removable Doors
- Order Preloaded with Terminated Cables, Adapters, Pigtails or Cassettes
- Rugged 14 Gauge Aluminum, Available in Black or Off-White (BW)

The 1RU FIS Rack Mount Enclosure provides many flexible configurations in a 1RU form factor. It accommodates (3) LGX adapter plates, modules or cassettes. Slide out trays and removable front and back doors allow easy access to the patch bay. Multiple cable retention brackets and tie down spots allow for convenient cable management. Spring loaded stop latches keep the tray securely in place when retracted. Rack mount installs into a standard 19" rack. Adapter plates, 23" mounting brackets and 19" flush mounting brackets are sold separately.

### **SPECIFICATIONS**

Dimensions	17"W x 14"D x 1.75"H
Capacity	Up to 18 (6 Pack) or 24 (8 Pack) Simplex Connections Up to 36 (6 Pack) Duplex Connections (LC or SC)
Material	.060" Aluminum
Coatings	Electro-statically Applied Powder Coat, Available in Black or Off White

### ORDERING INFORMATION

F1-RM1RU3X	1RU Rack Mount, 3 Plates, Solid Front/Rear Doors, Black
F1-RM1RU3X-BW	1RU Rack Mount, 3 Plates, Solid Front/Rear Doors, Off White

## ACCESSORIES (PURCHASED SEPARATELY)

RACK-ADP23	1RU and 2RU 23" Rack Mounting Brackets, Pair, Black
RACK-ADP23BW	1RU and 2RU 23" Rack Mounting Brackets, Pair, Off White
F1-SPL12	Metal Splice Tray, 12 Position Fusion Splice Chip, 6.5"L x 4.7"W x .42"H
F1-SPL24	Metal Splice Tray, 24 Position Fusion Splice Chip, 11.72"L x 3.99"W x .42"H
F1-6808	Plastic Splice Tray, 12 Position Fusion Splice Chip, 7.1"L x 4.25"W x .48"H
F1-6707BLKF	Metal Splice Tray, 12 Position Fusion Splice Chip, 7.5″L x 4″W x .63″H
F1-13187	Cable Retention Rings For 1RU & 2RU Interconnect (10 Pack)
F1-MCMB	Metal Cable Management Spools (Pair)