

## SACC-M 8FS-4CON-M-SW

Order No.: 1506891

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1506891>

Sensor/actuator connector, female, straight, 4-pos., M8, screw connection, metal knurl, cable diameter max. 5 mm

### Commercial data

EAN	4017918881207
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.0114 KG
Catalog page information	Page 41 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
03/21/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

Nominal current $I_N$	4 A
Nominal voltage $U_N$	30 V
Number of positions	4
Volume resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$

Ambient temperature (operation)	-40 °C ... 85 °C (plug/socket)
<b>General characteristics</b>	
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PUR / PA66
Material of grip body	PBT
Material, knurls	Nickel-plated brass
Sealing material	NBR
Type of connection	Screw connection
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	0.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	20
Min. diameter	3.5 mm
Max. diameter	5 mm
Status display	No

### Certificates / Approvals



Certification GOST


### Accessories

Item	Designation	Description
<b>General</b>		
1436945	SACC-M 8-SET/2,2-3,5	Sensor/actuator connector, accessories, pressure screw and seal, for unshielded M8 connector, cable diameter 2.2 mm - 3.5 mm

**Diagrams/Drawings**


Dimensioned drawing

Socket M8 x 1, straight



Schematic diagram

Pin assignment M8 socket, 4-pos., view female side



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;